

## CARMEN-50-RS-C-WHT

~11° spot beam. Assembly with holder C compatible with LEDiL HEKLA. White version.

## SPECIFICATION:

|                |           |
|----------------|-----------|
| Dimensions     | Ø 50.0 mm |
| Height         | 25.5 mm   |
| Fastening      | socket    |
| ROHS compliant | yes ⓘ     |




## MATERIALS:

| Component           | Type        | Material | Colour | Finish | Length |
|---------------------|-------------|----------|--------|--------|--------|
| CARMEN-50-RS        | Single lens | PMMA     | clear  |        | 47.0   |
| CARMEN-50-HLD-C-WHT | Holder      | PC       | white  |        | 50.0   |

## ORDERING INFORMATION:

| Component                      |             | Qty in box | MOQ | MPQ | Box weight (kg) |
|--------------------------------|-------------|------------|-----|-----|-----------------|
| CP16632_CARMEN-50-RS-C-WHT     | Single lens | 308        | 112 | 28  | 7.2             |
| » Box size: 476 x 273 x 292 mm |             |            |     |     |                 |




See also our general installation guide: [www.ledil.com/installation\\_guide](http://www.ledil.com/installation_guide)

#### OPTICAL RESULTS (MEASURED):





LED Vesta TW 6mm DP  
 FWHM / FWTM 11.0° / 21.0°  
 Efficiency 81 %  
 Peak intensity 10.4 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:  
 C16142\_HEKLA-SOCKET-K  
 Bender Wirth: 504 Typ L8



Light distribution files

#### CITIZEN



LED CLU700/701/702/703  
 FWHM / FWTM 11.0° / 22.0°  
 Efficiency 88 %  
 Peak intensity 11.4 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:  
 F15255\_HEKLA-SOCKET-C



Light distribution files

#### CITIZEN

LED CLU710/711  
 FWHM / FWTM 14.0° / 28.0°  
 Efficiency 84 %  
 Peak intensity 6.7 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:  
 F15859\_HEKLA-SOCKET-I




Light distribution files

#### OPTICAL RESULTS (MEASURED):

#### CITIZEN


LED CLU7B2  
 FWHM / FWTM 8.0° / 17.0°  
 Efficiency 89 %  
 Peak intensity 21.2 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:  
 F15255\_HEKLA-SOCKET-C



Light distribution files





LED CXA/B 13xx  
 FWHM / FWTM 12.0° / 23.0°  
 Efficiency 87 %  
 Peak intensity 11.1 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:  
 F15956\_HEKLA-SOCKET-J



Light distribution files



LED LUXEON CX Plus CoB - HD S01H4  
 FWHM / FWTM 10.0° / 19.0°  
 Efficiency 88 %  
 Peak intensity 13.7 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:  
 Bender Wirth: 634c Hekla




Light distribution files



#### OPTICAL RESULTS (MEASURED):





LED LUXEON CX Plus CoB - HD S02H6  
 FWHM / FWTM 10.0° / 20.0°  
 Efficiency 88 %  
 Peak intensity 12.2 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:  
 Bender Wirth: 634c Hekla



Light distribution files




LED LUXEON CX Plus CoB - HD S04H9  
 FWHM / FWTM 15.0° / 27.0°  
 Efficiency 87 %  
 Peak intensity 6 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:  
 Bender Wirth: 634c Hekla



Light distribution files



LED LUXEON CX Plus CoB M02 / M03 (Gen2)  
 FWHM / FWTM 13.0° / 25.0°  
 Efficiency 86 %  
 Peak intensity 7.1 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:  
 Bender Wirth: 641a Hekla




Light distribution files

#### OPTICAL RESULTS (MEASURED):




LED LUXEON CX Plus CoB S01 (Gen2)  
 FWHM / FWTM 10.0° / 19.0°  
 Efficiency 88 %  
 Peak intensity 14 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:  
 Bender Wirth: 634c Hekla



Light distribution files





LED CXM-3  
 FWHM / FWTM 8.0° / 17.0°  
 Efficiency 91 %  
 Peak intensity 20.9 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:  
 F15255\_HEKLA-SOCKET-C



Light distribution files



LED CXM-4  
 FWHM / FWTM 9.0° / 18.0°  
 Efficiency 87 %  
 Peak intensity 15.7 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:  
 F15255\_HEKLA-SOCKET-C




Light distribution files

#### OPTICAL RESULTS (MEASURED):

#### XICATO



LED XOB 6 mm  
 FWHM / FWTM 12.0° / 24.0°  
 Efficiency 85 %  
 Peak intensity 9.6 cd/m  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:  
 F15255\_HEKLA-SOCKET-C



Light distribution files

#### XICATO

LED XOB 9.8 mm  
 FWHM / FWTM 15.0° / 29.0°  
 Efficiency 85 %  
 Peak intensity 6.1 cd/m  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:  
 F15255\_HEKLA-SOCKET-C




Light distribution files

#### OPTICAL RESULTS (SIMULATED):

#### CITIZEN


LED CLL02x/CLU02x (LES10)  
 FWHM / FWTM 15.0° / 30.0°  
 Efficiency 87 %  
 Peak intensity 6.6 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:  
 F15255\_HEKLA-SOCKET-C



Light distribution files




LED CMU15xx  
 FWHM / FWTM 26.0° / 54.0°  
 Efficiency 91 %  
 Peak intensity 2.7 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:  
 F17438\_HEKLA-G2-I



Light distribution files



LED CMU15xx  
 FWHM / FWTM 27.0° / 56.0°  
 Efficiency 91 %  
 Peak intensity 2.6 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:  
 F17438\_HEKLA-G2-I




Light distribution files

#### OPTICAL RESULTS (SIMULATED):




LED LUXEON CoB 1202/1203  
 FWHM / FWTM 16.0° / 30.0°  
 Efficiency 88 %  
 Peak intensity 6.5 cd/Im  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:  
 F15858\_HEKLA-SOCKET-H



Light distribution files




LED LUXEON CoB 1204HD  
 FWHM / FWTM 16.0° / 30.0°  
 Efficiency 88 %  
 Peak intensity 6 cd/Im  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:  
 F15858\_HEKLA-SOCKET-H



Light distribution files



LED MJT COB LES 6  
 FWHM / FWTM 11.0° / 25.0°  
 Efficiency 92 %  
 Peak intensity 12.7 cd/Im  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:  
 F15255\_HEKLA-SOCKET-C




Light distribution files

#### OPTICAL RESULTS (SIMULATED):



LED MJT COB LES 9.8  
 FWHM / FWTM 20.0° / 36.0°  
 Efficiency 91 %  
 Peak intensity 5.4 cd/Im  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:  
 F15255\_HEKLA-SOCKET-C



Light distribution files

### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B  
Casic Motor Building  
Shenzhen 518057  
P.R.CHINA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Poznan, Poland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)