

# 0401 KSS SPIRAL WRAPPING BAND

- Color: Standard in natural. Black and other colors are available upon request.
- Description:
  1. Flexible construction enable bands to follow wire ways easily.
  2. Durable, reusable with retained spiral strength.
  3. Fix ends of band with KSS cable ties and spiral wire bundles in clockwise direction to complete works.
  4. Expand spiral range almost without limit. An economical way of cable binding. Easily applied to electric harness, cables and wire bundles. Cut-to-fit versatility in convenient roll-form.
- A reverse design is available.



Box



KSP

Spool Pack

## ◆ PE

UNIT : mm

Item No.		O.D.	T	W	Wrapping Range	Packing
Natural	Black					
KS-3	KS-3BK	3.0	0.5	4.7	1.5~10	10M / Bag
KS-6	KS-6BK	4.5	0.6	6.7	2.5~15	
KS-6L	KS-6LBK	6.0	0.6	7.4	4~25	
KS-6.5	KS-6.5BK	6.5	0.55	7.9	5~25	
KS-8	KS-8BK	8.0	0.75	12.0	6~30	
KS-10	KS-10BK	10.0	0.8	12.3	7.5~30	
KS-12	KS-12BK	12.0	0.85	15.0	9~32	
KS-15	KS-15BK	15.0	1.0	15.5	12~35	
KS-19	KS-19BK	19.0	1.2	19.2	15~50	
KS-24	KS-24BK	24.0	1.3	21.5	20~100	
<b>NEW</b> KS-32	<b>NEW</b> KS-32BK	32.0	1.5	25.0	28~120	

## ◆ PE / BOX PACK


Item No.	O.D.	T	W	Wrapping Range	Packing (Box)
<b>NEW</b> KS-8-400M	8.0	0.75	12.0	6~30	400M
<b>NEW</b> KS-10-250M	10.0	0.8	12.3	7.5~30	250M
<b>NEW</b> KS-12-170M	12.0	0.85	15.0	9~32	170M
<b>NEW</b> KS-15-120M	15.0	1.0	15.5	12~35	120M
<b>NEW</b> KS-19-80M	19.0	1.2	19.2	15~50	80M
<b>NEW</b> KS-24-50M	24.0	1.3	21.5	20~100	50M

## ◆ PE / SPOOL PACK

Item No.	O.D.	T	W	Wrapping Range	Packing
KSP-3	3.0	0.5	4.7	1.5~10	100 FT (30.5M) / Roll
KSP-6	4.5	0.6	6.7	2.5~15	
KSP-6L	6.0	0.6	7.4	4~25	
KSP-6.5	6.5	0.55	7.9	5~25	
KSP-8	8.0	0.75	12.0	6~30	
KSP-10	10.0	0.8	12.3	7.5~30	
KSP-12	12.0	0.85	15.0	9~32	
KSP-15	15.0	1.0	15.5	12~35	
KSP-19	19.0	1.2	19.2	15~50	
KSP-24	24.0	1.3	21.5	20~100	

## ◆ NYLON 6 (UL 94HB)

Item No.	O.D.	T	W	Wrapping Range	Packing
KS-6N6	4.5	0.45	8.0	4~25	10M / Bag
<b>NEW</b> KS-6LN6	6.0	0.52	8.0	4~25	
KS-6.5N6	6.5	0.55	7.4	5~25	
KS-8N6	8.0	0.7	12.0	6~30	
KS-10N6	10.0	0.7	12.5	7.5~30	
KS-12N6	12.0	0.7	16.0	9~32	
KS-15N6	15.0	0.8	16.8	12~35	
KS-19N6	19.0	0.9	19.4	15~50	
KS-24N6	24.0	0.9	20.5	20~100	



O.D. AS PRODUCTION (BEFORE CUT IN LENGTH)  
Standard design