

Click to
ORDER
samples

AM1LR-LPZ



SMD Package

The AM1LR-LPZ is a 1W SMD DC/DC converter that offers great cost savings thanks to an improved manufacturing process. It also features excellent reliability and performance while offering a standard input voltage range of 5-24VDC as well as an output voltage of 3.3-24V. This compact SMD design will surely benefit your new system design.


This new series offers great operating temperatures, from -40 to 85°C with full power up to 71°C. Also, the isolations of 1500VDC and 3000VDC for improved reliability and system safety as well as a great 3,500,000h MTBF come standard.

The AM1LR-LPZ is suitable for instrumentation, industrial controls, industrial applications, communication and IoT applications.

Features

- High I/O Isolation of 1500/3000VDC
- Continuous Short circuit protection
- Operating Temp: -40 °C to +85 °C
- Low profile case height: 7.25mm
- Compact footprint and high-power density
- Efficiency up to 71%
- Regulated output

Summary



Training



Product Training Video
(click to open)



Press Release

Coming Soon!

Application Notes

Applications



IoT



Industrial



Telecom



Portable Equipment

Models & Specifications



Single Output

Model	Input Voltage (VDC)	Output Voltage (VDC)	Input Current Full No load typ. (mA)	Output Current max min (mA)*	Isolation (VDC)	Maximum capacitive Load (μF)	Efficiency Typ. (%)
AM1LR-0503SLPZ	5 (4.75-5.25)	3.3	290 / 6	250/25	1500	2400	66
AM1LR-0505SLPZ	5 (4.75-5.25)	5	290 / 6	200/20	1500	2400	69
AM1LR-0509SLPZ	5 (4.75-5.25)	9	290 / 6	111/12	1500	1000	70
AM1LR-0512SLPZ	5 (4.75-5.25)	12	290 / 6	84/9	1500	560	71
AM1LR-0515SLPZ	5 (4.75-5.25)	15	290 / 6	67/7	1500	560	71
AM1LR-0524SLPZ	5 (4.75-5.25)	24	290 / 6	41/4	1500	100	71
AM1LR-1205SLPZ	12 (11.4-12.6)	5	120 / 6	200/20	1500	2400	69
AM1LR-1212SLPZ	12 (11.4-12.6)	12	120 / 6	84/9	1500	560	71
AM1LR-1215SLPZ	12 (11.4-12.6)	15	120 / 6	67/7	1500	220	71
AM1LR-1505SLPZ	15 (14.25-15.75)	5	100 / 6	200/20	1500	2400	68
AM1LR-2405SLPZ	24 (22.8-25.2)	5	60 / 6	200/20	1500	2400	69
AM1LR-2412SLPZ	24 (22.8-25.2)	12	60 / 6	84/9	1500	560	71
AM1LR-2415SLPZ	24 (22.8-25.2)	15	60 / 6	67/7	1500	220	71
AM1LR-0503SH30LPZ	5 (4.75-5.25)	3.3	290 / 6	250 / 25	3000	2400	66
AM1LR-0505SH30LPZ	5 (4.75-5.25)	5	290 / 6	200 / 20	3000	2400	69
AM1LR-0509SH30LPZ	5 (4.75-5.25)	9	290 / 6	111 / 12	3000	1000	70
AM1LR-0512SH30LPZ	5 (4.75-5.25)	12	290 / 6	84 / 9	3000	560	71
AM1LR-0515SH30LPZ	5 (4.75-5.25)	15	290 / 6	67 / 7	3000	560	71
AM1LR-0524SH30LPZ	5 (4.75-5.25)	24	290 / 6	41 / 4	3000	100	71
AM1LR-1205SH30LPZ	12 (11.4-12.6)	5	120 / 6	200 / 20	3000	2400	69
AM1LR-1212SH30LPZ	12 (11.4-12.6)	12	120 / 6	84 / 9	3000	560	71
AM1LR-1215SH30LPZ	12 (11.4-12.6)	15	120 / 6	67 / 7	3000	220	71
AM1LR-1505SH30LPZ	15 (14.25-15.75)	5	100 / 6	200 / 20	3000	2400	68
AM1LR-2405SH30LPZ	24 (22.8-25.2)	5	60 / 6	200 / 20	3000	2400	69
AM1LR-2412SH30LPZ	24 (22.8-25.2)	12	60 / 6	84 / 9	3000	560	71
AM1LR-2415SH30LPZ	24 (22.8-25.2)	15	60 / 6	67 / 7	3000	220	71

* Performance will be degraded if the load is not within the output current range.

Input Specification

Parameters	Conditions	Typical	Maximum	Units
Filter	Capacitor			
Input reflected ripple current		30		mA

Isolation Specification

Parameters	Conditions	Typical	Maximum	Units
Tested I/O voltage	60 sec, leakage ≤ 1mA	>1500		VDC
	60 sec, leakage ≤ 1mA, for H30 models	>3000		VDC
Resistance	500VDC	>1000		MΩ
Capacitance	100kHz/0.1V	20		pF

Output Specification

Parameters	Conditions	Typical	Maximum	Units
Voltage accuracy	100% load		±3	%
Line regulation	Per 1% Vin change		±0.25	%
Load regulation	10-100% load, 3.3Vout		±3	%
	10-100% load, others		±2	%
Ripple & Noise*		30	100	mV pk-pk
Temperature coefficient		±0.02		%/°C

* Ripple and Noise are measured at 20MHz bandwidth. Please refer to the application note for specific details.

General Specifications


Parameters	Conditions	Typical	Maximum	Units
Switching frequency	Full load, nominal input	260		KHz
Short circuit protection	Continuous, Auto recovery			
Operating temperature	With derating at 71°C	-40 to +85		°C
Storage temperature		-55 to +125		°C
Case temperature rise	Ambient temperature at 25°C	25		°C
Reflow soldering temperature	Maximum duration 60s when over 217°C		245	°C
Soldering method	IPC/JEDEC J-STD-020D.1.			
Cooling	Free air convection			
Humidity	Non-condensing	>5	95	% RH
Vibration	10-150Hz, 5G, 0.75mm along all axis			
Moisture sensitivity level	Level 1			
Case material	Black plastic (flammability to UL 94V-0)			
Weight		1.7		g
Dimensions (L x W x H)		0.6 x 0.45 x 0.28 inches (15.24 x 11.40 x 7.25 mm)		
MTBF	3 500 000 hrs (MIL-HDBK -217F, t=+25°C) / Full Load			

NOTE: All specifications in this datasheet are measured at an ambient temperature of 25°C, humidity<75%, nominal input voltage and at rated output load unless otherwise specified.


Safety Specifications

Parameters		
Standards	Information technology Equipment	Design to meet UL/EN/IEC 62368-1
	EMC - Conducted and radiated emission	CISPR32 / EN55032, class B with the recommended EMI circuit
	Electrostatic Discharge Immunity	IEC 61000-4-2 Air ±8KV, Contact ±4KV, Criteria B

Derating




Typical application circuit





Vin	Cin	Vout	Cout
5	4.7μF/25V	3.3/5V	10μF, 16V
12	2.2μF/16V	9/12V	2.2μF, 25V
15	1μF/25V	15V	1μF, 50V
24	1μF/50V	24V	1μF, 50V

EMI Recommended circuit



Model	C1/C2	CY
1500VDC models	4.7μF/50V	1nF/2kVdc
3000VDC models	4.7μF/50V	270pF/3kVdc

Dimensions



Pin Out Specifications	
Pin	Single
1	-V Input
2	+V Input
4	-V Output
5	-V Output
7	+V Output
10	NC

Note:
 Unit: mm(inch)
 General tolerance: ± 0.25 (0.01)
 Pin tolerance: ± 0.1 (0.004)

NOTE: **1.** Datasheets are updated as needed and as such, specifications are subject to change without notice. Once printed or downloaded, datasheets are no longer controlled by Aimtec; refer to www.aimtec.com for the most current product specifications. **2.** Product labels shown, including safety agency certifications on labels, may vary based on the date manufactured. **3.** Mechanical drawings and specifications are for reference only. **4.** All specifications are measured at an ambient temperature of 25°C, humidity<75%, nominal input voltage and at rated output load unless otherwise specified. **5.** Aimtec may not have conducted destructive testing or chemical analysis on all internal components and chemicals at the time of publishing this document. CAS numbers and other limited information are considered proprietary and may not be available for release. **6.** This product is not designed for use in critical life support systems, equipment used in hazardous environments, nuclear control systems or other such applications which necessitate specific safety and regulatory standards other the ones listed in this datasheet. **7.** Warranty is in accordance with Aimtec's standard Terms of Sale available at www.aimtec.com.