

DAISY-7X1-WW

~80° wide beam. Choose SHD with no lips or SHD2 with narrow lips and square openings. SHD3 with narrow lips and round openings.

SPECIFICATION:

Dimensions	279.5 x 39.6
Height	20.3 mm
Fastening	pin, screw, clips
ROHS compliant	yes ⓘ



MATERIALS:

Component	Type	Material	Colour	Finish	Length (mm)
C16870_DAISY-7X1-WW	Linear lens	PMMA	clear		
L20015_DAISY-7X1-SHD2-MET-MATT	Shade	PC-ABS	metal	matt	
L20014_DAISY-7X1-SHD2-MET	Shade	PC	metal	gloss	
L20013_DAISY-7X1-SHD2-MATT-WHT	Shade	PC	white	matt	
L20012_DAISY-7X1-SHD2-WHT	Shade	PC	white	gloss	
L20011_DAISY-7X1-SHD2-MATT	Shade	PC-ABS	black	matt	
L20010_DAISY-7X1-SHD2	Shade	PC	black	gloss	
C19855_DAISY-7X1-SHD3-MATT-GLD	Shade	PC	gold	matt	
C19854_DAISY-7X1-SHD3-MATT-RED	Shade	PC	red	matt	
C19853_DAISY-7X1-SHD3-MATT-GR	Shade	PC	grey	matt	
C19852_DAISY-7X1-SHD-MATT-GLD	Shade	PC	gold	matt	
C19764_DAISY-7X1-SHD-MATT-GR	Shade	PC	grey	matt	
C19763_DAISY-7X1-SHD-MATT-RED	Shade	PC	red	matt	
C19642_DAISY-7X1-SHD3-MET-MATT	Shade	PC	metal	matt	
C19641_DAISY-7X1-SHD3-MET	Shade	PC	metal	gloss	
C19315_DAISY-7X1-SHD3-WHT-MATT	Shade	PC	white	matt	
C19314_DAISY-7X1-SHD3-WHT	Shade	PC	white	gloss	
C19313_DAISY-7X1-SHD3-MATT	Shade	PC	black	matt	

C18469_DAISSY-7X1-SHD-MET-MATT	Shade	PC	metal	matt
C18167_DAISSY-7X1-SHD-MET	Shade	PC	metal	gloss
C17225_DAISSY-7X1-SHD-WHT-MATT	Shade	PC	white	matt
C17051_DAISSY-7X1-SHD-MATT	Shade	PC	black	matt
C16876_DAISSY-7X1-SHD-WHT	Shade	PC	white	gloss
C16872_DAISSY-7X1-SHD	Shade	PC	black	gloss

ORDERING INFORMATION:



Quantities for one set:


Linear lens 1

Shade 1

Component		Qty in box	MOQ	MPQ	Box weight (kg)
C16870_DAISY-7X1-WW » Box size: 400 x 300 x 300 mm	Linear lens	312	312	24	5.6
L20010_DAISY-7X1-SHD2 » Box size: 595 x 360 x 230 mm	Shade	156	312	24	6.9
C19315_DAISY-7X1-SHD3-WHT-MATT » Box size: 595 x 360 x 230 mm	Shade	156	312	24	6.2
C16872_DAISY-7X1-SHD » Box size: 595 x 360 x 230 mm	Shade	156	312	24	7.1
L20015_DAISY-7X1-SHD2-MET-MATT » Box size: 595 x 360 x 230 mm	Shade	156	312	24	6.6
C19852_DAISY-7X1-SHD-MATT-GLD » Box size: 595 x 360 x 230 mm	Shade	156	312	24	7.1
C18409_DAISY-7X1-SHD-MET-MATT » Box size: 595 x 360 x 230 mm	Shade	156	312	24	7.0
L20011_DAISY-7X1-SHD2-MATT » Box size: 595 x 360 x 230 mm	Shade	156	312	24	6.7
C19641_DAISY-7X1-SHD3-MET » Box size: 595 x 360 x 230 mm	Shade	156	312	24	6.1
C16876_DAISY-7X1-SHD-WHT » Box size: 595 x 360 x 230 mm	Shade	156	312	24	7.6
C19853_DAISY-7X1-SHD3-MATT-GR » Box size: 595 x 360 x 230 mm	Shade	156	312	24	7.1
C19312_DAISY-7X1-SHD3 » Box size: 595 x 360 x 230 mm	Shade	156	312	24	6.1
L20012_DAISY-7X1-SHD2-WHT » Box size: 595 x 360 x 230 mm	Shade	156	312	24	8.2
C19642_DAISY-7X1-SHD3-MET-MATT » Box size: 595 x 360 x 230 mm	Shade	156	312	24	5.7
C17051_DAISY-7X1-SHD-MATT » Box size: 595 x 360 x 230 mm	Shade	156	312	24	7.3
C19854_DAISY-7X1-SHD3-MATT-RED » Box size: 595 x 360 x 230 mm	Shade	156	312	24	6.2
C19313_DAISY-7X1-SHD3-MATT » Box size: 595 x 360 x 230 mm	Shade	156	312	24	5.8
L20013_DAISY-7X1-SHD2-MATT-WHT » Box size: 595 x 360 x 230 mm	Shade	156	312	24	8.2
C19763_DAISY-7X1-SHD-MATT-RED » Box size: 595 x 360 x 230 mm	Shade	156	312	24	7.1

C19855_DAISY-7X1-SHD3-MATT-GLD » Box size: 595 x 360 x 230 mm	Shade	156	312	24	6.2
C19314_DAISY-7X1-SHD3-WHT » Box size: 595 x 360 x 230 mm	Shade	156	312	24	6.3
L20014_DAISY-7X1-SHD2-MET » Box size: 595 x 360 x 230 mm	Shade	156	312	24	8.2
C19764_DAISY-7X1-SHD-MATT-GR » Box size: 595 x 360 x 230 mm	Shade	156	312	24	5.7
C18167_DAISY-7X1-SHD-MET » Box size: 595 x 360 x 230 mm	Shade	156	312	24	7.0







See also our general installation guide: www.ledil.com/installation_guide

OPTICAL RESULTS (MEASURED):





LED LIGHT ENGINE DAISY 28 LEDs 277.5mm x 20mm
FWHM / FWTM 76.0° / 88.0°
Efficiency 95 %
Peak intensity 0.7 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
C16876_DAISY-7X1-SHD-WHT



Light distribution files





LED LIGHT ENGINE DAISY 28 LEDs 277.5mm x 20mm
FWHM / FWTM 76.0° / 88.0°
Efficiency 95 %
Peak intensity 0.7 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
C17225_DAISY-7X1-SHD-WHT-MATT



Light distribution files



LED LIGHT ENGINE DAISY 28 LEDs 277.5mm x 20mm
FWHM / FWTM 75.0° / 87.0°
Efficiency 94 %
Peak intensity 0.7 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
C17533_DAISY-7X1-SHD-MET-MATT




Light distribution files

OPTICAL RESULTS (MEASURED):





LED LIGHT ENGINE DAISY 28 LEDs 277.5mm x 20mm
FWHM / FWTM 76.0° / 87.0°
Efficiency 87 %
Peak intensity 0.6 cd/m
LEDs/each optic 4
Light colour/type White
Required components:
C16872_DAISSY-7X1-SHD



Light distribution files





LED LIGHT ENGINE DAISY 28 LEDs 277.5mm x 20mm
FWHM / FWTM 76.0° / 87.0°
Efficiency 86 %
Peak intensity 0.6 cd/m
LEDs/each optic 4
Light colour/type White
Required components:
C17051_DAISSY-7X1-SHD-MATT



Light distribution files



LED LIGHT ENGINE DAISY 28 LEDs 277.5mm x 20mm
FWHM / FWTM 74.0° / 87.0°
Efficiency 96 %
Peak intensity 0.7 cd/m
LEDs/each optic 4
Light colour/type White
Required components:
C18167_DAISSY-7X1-SHD-MET





Light distribution files

OPTICAL RESULTS (MEASURED):

inventronics


LED PL-LIN-2000 280x24mm
FWHM / FWTM 75.0° / 87.0°
Efficiency 85 %
Peak intensity 0.6 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
C17051_DAISSY-7X1-SHD-MATT



Light distribution files

LUMILEDS



LED LUXEON 2835 Line
FWHM / FWTM 76.0° / 88.0°
Efficiency 95 %
Peak intensity 0.7 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
C16876_DAISSY-7X1-SHD-WHT



Light distribution files

LUMILEDS

LED LUXEON 2835 Line
FWHM / FWTM 76.0° / 88.0°
Efficiency 95 %
Peak intensity 0.7 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
C17225_DAISSY-7X1-SHD-WHT-MATT




Light distribution files

OPTICAL RESULTS (MEASURED):




LED LUXEON 2835 Line
FWHM / FWTM 75.0° / 87.0°
Efficiency 94 %
Peak intensity 0.7 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
 C17533_DAISSY-7X1-SHD-MET-MATT



Light distribution files





LED LUXEON 2835 Line
FWHM / FWTM 76.0° / 87.0°
Efficiency 87 %
Peak intensity 0.6 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
 C16872_DAISSY-7X1-SHD



Light distribution files



LED LUXEON 2835 Line
FWHM / FWTM 76.0° / 87.0°
Efficiency 86 %
Peak intensity 0.6 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
 C17051_DAISSY-7X1-SHD-MATT





Light distribution files

OPTICAL RESULTS (MEASURED):





LED LUXEON 2835 Line
FWHM / FWTM 74.0° / 87.0°
Efficiency 96 %
Peak intensity 0.7 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
 C17532_DAISSY-7X1-SHD-MET



Light distribution files





LED Opticus Daisy M L28W2
FWHM / FWTM 76.0° / 88.0°
Efficiency 86 %
Peak intensity 0.6 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
 C17051_DAISSY-7X1-SHD-MATT



Light distribution files



LED LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1
FWHM / FWTM 76.0° / 88.0°
Efficiency 85 %
Peak intensity 0.6 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
 C17051_DAISSY-7X1-SHD-MATT





Light distribution files

OPTICAL RESULTS (MEASURED):

MST | *Your solutions*


LED LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1
 FWHM / FWTM 76.0° / 87.0°
 Efficiency 86 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 4
 Light colour/type White
 Required components:
 C16872_DAISY-7X1-SHD



Light distribution files

MST | *Your solutions*



LED LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1
 FWHM / FWTM 75.0° / 87.0°
 Efficiency 95 %
 Peak intensity 0.7 cd/lm
 LEDs/each optic 4
 Light colour/type White
 Required components:
 C18167_DAISY-7X1-SHD-MET



Light distribution files

MST | *Your solutions*

LED LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1
 FWHM / FWTM 76.0° / 88.0°
 Efficiency 94 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 4
 Light colour/type White
 Required components:
 C17225_DAISY-7X1-SHD-WHT-MATT





Light distribution files

OPTICAL RESULTS (MEASURED):

MST | *Your solutions*


LED LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1
FWHM / FWTM 77.0° / 88.0°
Efficiency 94 %
Peak intensity 0.6 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
C16876_DAISY-7X1-SHD-WHT



Light distribution files

MST | *Your solutions*



LED LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1
FWHM / FWTM 75.0° / 88.0°
Efficiency 94 %
Peak intensity 0.7 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
C17533_DAISY-7X1-SHD-MET-MATT



Light distribution files

MST | *Your solutions*

LED LinLED 280x28mm 1600lm 840 4C 21V DAISY 7x1(ZT25)
FWHM / FWTM 77.0° / 82.0°
Efficiency 86 %
Peak intensity 0.6 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
C16872_DAISY-7X1-SHD





Light distribution files

OPTICAL RESULTS (MEASURED):

MST | *Your solutions*



LED LinLED 280x28mm 2x550lm 827-865 2x2C 42V DAISY-7X
 FWHM / FWTM 76.0° / 88.0°
 Efficiency 94 %
 Peak intensity 0.7 cd/lm
 LEDs/each optic 4
 Light colour/type Tunable White
 Required components:
 C17533_DAISSY-7X1-SHD-MET-MATT



Light distribution files

MST | *Your solutions*



LED LinLED 280x28mm 2x550lm 827-865 2x2C 42V DAISY-7X
 FWHM / FWTM 76.0° / 88.0°
 Efficiency 87 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 4
 Light colour/type Tunable White
 Required components:
 C16872_DAISSY-7X1-SHD



Light distribution files

MST | *Your solutions*

LED LinLED 280x28mm 2x550lm 827-865 2x2C 42V DAISY-7X
 FWHM / FWTM 76.0° / 88.0°
 Efficiency 86 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 4
 Light colour/type Tunable White
 Required components:
 C17051_DAISSY-7X1-SHD-MATT





Light distribution files

OPTICAL RESULTS (MEASURED):

MST | *Your solutions*



LED LinLED 280x28mm 2x550lm 827-865 2x2C 42V DAISY-7X
 FWHM / FWTM 75.0° / 88.0°
 Efficiency 95 %
 Peak intensity 0.7 cd/lm
 LEDs/each optic 4
 Light colour/type Tunable White
 Required components:
 C18167_DAISSY-7X1-SHD-MET



Light distribution files

MST | *Your solutions*


LED LinLED 280x28mm 2x550lm 827-865 2x2C 42V DAISY-7X
 FWHM / FWTM 77.0° / 89.0°
 Efficiency 95 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 4
 Light colour/type Tunable White
 Required components:
 C16876_DAISSY-7X1-SHD-WHT



Light distribution files

MST | *Your solutions*

LED LinLED 280x28mm 2x550lm 827-865 2x2C 42V DAISY-7X
 FWHM / FWTM 77.0° / 89.0°
 Efficiency 95 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 4
 Light colour/type Tunable White
 Required components:
 C17225_DAISSY-7X1-SHD-WHT-MATT




Light distribution files

OPTICAL RESULTS (MEASURED):





LED NF2W757G-MT (Tunable White)
FWHM / FWTM 80.0° / 86.0°
Efficiency 96 %
Peak intensity 0.6 cd/lm
LEDs/each optic 1
Light colour/type Tunable White
Required components:
 C16876_DAISSY-7X1-SHD-WHT



Light distribution files





LED NF2W757G-MT (Tunable White)
FWHM / FWTM 79.0° / 85.0°
Efficiency 86 %
Peak intensity 0.6 cd/lm
LEDs/each optic 1
Light colour/type Tunable White
Required components:
 C16872_DAISSY-7X1-SHD



Light distribution files



LED NFSx757G
FWHM / FWTM 75.0° / 86.0°
Efficiency 88 %
Peak intensity 0.6 cd/lm
LEDs/each optic 4
Light colour/type Tunable White
Required components:
 C16872_DAISSY-7X1-SHD




Light distribution files

OPTICAL RESULTS (MEASURED):

OSRAM
Opto Semiconductors



LED OSCONIQ E 2835
FWHM / FWTM 76.0° / 87.0°
Efficiency 86 %
Peak intensity 0.6 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
C17051_DAISSY-7X1-SHD-MATT



Light distribution files

SAMSUNG



LED LM28xB Series
FWHM / FWTM 77.0° / 85.0°
Efficiency 88 %
Peak intensity 0.6 cd/lm
LEDs/each optic 2
Light colour/type White
Required components:
C16872_DAISSY-7X1-SHD



Light distribution files

SAMSUNG

LED LM28xB Series
FWHM / FWTM 78.0° / 86.0°
Efficiency 94 %
Peak intensity 0.6 cd/lm
LEDs/each optic 2
Light colour/type White
Required components:
C17225_DAISSY-7X1-SHD-WHT-MATT





Light distribution files

OPTICAL RESULTS (MEASURED):

SAMSUNG

LED LM28xB Series
 FWHM / FWTM 78.0° / 86.0°
 Efficiency 94 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 2
 Light colour/type White
 Required components:
 C16876_DAISY-7X1-SHD-WHT





Light distribution files

SEITEC

Elektronik GmbH

LED LED-St-L28W2c4-xxx-C015-55 (DAISY-7x1)
 FWHM / FWTM 76.0° / 87.0°
 Efficiency 87 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 4
 Light colour/type White
 Required components:
 C16872_DAISY-7X1-SHD





Light distribution files

SEITEC

Elektronik GmbH

LED LED-St-L28W2c4-xxx-C015-55 (DAISY-7x1)
 FWHM / FWTM 76.0° / 87.0°
 Efficiency 96 %
 Peak intensity 0.7 cd/lm
 LEDs/each optic 4
 Light colour/type White
 Required components:
 C17225_DAISY-7X1-SHD-WHT-MATT




Light distribution files

OPTICAL RESULTS (MEASURED):





LED LED-St-L28W2c4-xxx-C015-55 (DAISY-7x1)
FWHM / FWTM 75.0° / 87.0°
Efficiency 95 %
Peak intensity 0.7 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
C17533_DAISSY-7X1-SHD-MET-MATT



Light distribution files





LED LED-St-L28W2c4-xxx-C015-55 (DAISY-7x1)
FWHM / FWTM 76.0° / 87.0°
Efficiency 96 %
Peak intensity 0.7 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
C16876_DAISSY-7X1-SHD-WHT



Light distribution files






LED LED-St-L28W2c4-xxx-C015-55 (DAISY-7x1)
FWHM / FWTM 76.0° / 87.0°
Efficiency 86 %
Peak intensity 0.6 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
C17051_DAISSY-7X1-SHD-MATT



Light distribution files


OPTICAL RESULTS (MEASURED):



OPTICAL RESULTS (MEASURED):





LED PassivePAQ-L-1F35-SSA3-2.7K-840-3-DC
 FWHM / FWTM 80.0° / 90.0°
 Efficiency 85 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 4
 Light colour/type White
 Required components:
 C17051_DAISSY-7X1-SHD-MATT



Light distribution files





LED PassivePAQ-L-1F35-SSA3-2.7K-840-3-DC
 FWHM / FWTM 82.0° / 90.0°
 Efficiency 94 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 4
 Light colour/type White
 Required components:
 C17225_DAISSY-7X1-SHD-WHT-MATT



Light distribution files

TRIDONIC

LED LLE 24x280mm 750lm 8x0 LVD ADV1
 FWHM / FWTM 76.0° / 87.0°
 Efficiency 86 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 4
 Light colour/type White
 Required components:
 C17051_DAISSY-7X1-SHD-MATT





Light distribution files

OPTICAL RESULTS (MEASURED):

TRIDONIC


LED LLE 24x280mm 750lm 8x0 LVD ADV1
FWHM / FWTM 74.0° / 87.0°
Efficiency 96 %
Peak intensity 0.7 cd/lm
LEDs/each optic 4
Light colour/type Tunable White
Required components:
C18167_DAISSY-7X1-SHD-MET



Light distribution files

TRIDONIC



LED LLE 24x280mm 750lm 8x0 LVD ADV1
FWHM / FWTM 77.0° / 88.0°
Efficiency 95 %
Peak intensity 0.6 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
C17225_DAISSY-7X1-SHD-WHT-MATT



Light distribution files

TRIDONIC

LED LLE 24x280mm 750lm 8x0 LVD ADV1
FWHM / FWTM 77.0° / 88.0°
Efficiency 94 %
Peak intensity 0.6 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
C16876_DAISSY-7X1-SHD-WHT





Light distribution files

OPTICAL RESULTS (MEASURED):

TRIDONIC



LED LLE 24x280mm 750lm 8x0 LVD ADV1
FWHM / FWTM 76.0° / 87.0°
Efficiency 87 %
Peak intensity 0.6 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
C16872_DAISSY-7X1-SHD



Light distribution files

TRIDONIC

LED LLE 24x280mm 750lm 8x0 LVD ADV1
FWHM / FWTM 75.0° / 88.0°
Efficiency 95 %
Peak intensity 0.7 cd/lm
LEDs/each optic 4
Light colour/type Tunable White
Required components:
C17533_DAISSY-7X1-SHD-MET-MATT




Light distribution files

OPTICAL RESULTS (SIMULATED):




LED Bridgelux SMD 2835
FWHM / FWTM 76.0° / 88.0°
Efficiency 94 %
Peak intensity 0.7 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
C16876_DAISY-7X1-SHD-WHT



Light distribution files




LED Bridgelux SMD 5050
FWHM / FWTM 74.0° / 90.0°
Efficiency 94 %
Peak intensity 0.7 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
C16876_DAISY-7X1-SHD-WHT



Light distribution files



LED LUXEON 3030 HE Plus
FWHM / FWTM 80.0° / 85.0°
Efficiency 83 %
Peak intensity 0.6 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
C16872_DAISY-7X1-SHD




Light distribution files

OPTICAL RESULTS (SIMULATED):

MST | *Your solutions*


LED LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1
FWHM / FWTM 76.0° / 88.0°
Efficiency 94 %
Peak intensity 0.7 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
C17225_DAISSY-7X1-SHD-WHT-MATT



Light distribution files

MST | *Your solutions*


LED LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1
FWHM / FWTM 76.0° / 88.0°
Efficiency 92 %
Peak intensity 0.7 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
C18167_DAISSY-7X1-SHD-MET



Light distribution files

MST | *Your solutions*

LED LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1
FWHM / FWTM 76.0° / 88.0°
Efficiency 89 %
Peak intensity 0.7 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
C17051_DAISSY-7X1-SHD-MATT




Light distribution files

OPTICAL RESULTS (SIMULATED):

MST | *Your solutions*


LED LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1
FWHM / FWTM 76.0° / 88.0°
Efficiency 89 %
Peak intensity 0.7 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
C16872_DAISSY-7X1-SHD



Light distribution files

MST | *Your solutions*


LED LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1
FWHM / FWTM 76.0° / 88.0°
Efficiency 94 %
Peak intensity 0.7 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
C16876_DAISSY-7X1-SHD-WHT



Light distribution files

MST | *Your solutions*

LED LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1
FWHM / FWTM 76.0° / 88.0°
Efficiency 93 %
Peak intensity 0.7 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
C17533_DAISSY-7X1-SHD-MET-MATT




Light distribution files

OPTICAL RESULTS (SIMULATED):

NICHIA

LED	NF2W757G-MT (Tunable White)
FWHM / FWTM	76.0° / 88.0°
Efficiency	90 %
Peak intensity	0.7 cd/lm
LEDs/each optic	4
Light colour/type	Tunable White

Required components:
C16872_DAISSY-7X1-SHD




Light distribution files

NICHIA

LED	NF2W757G-MT (Tunable White)
FWHM / FWTM	77.0° / 86.0°
Efficiency	90 %
Peak intensity	0.7 cd/lm
LEDs/each optic	2
Light colour/type	Tunable White

Required components:
C16872_DAISSY-7X1-SHD




Light distribution files

OSRAM
Opto Semiconductors

LED	Duris E 2835
FWHM / FWTM	76.0° / 84.0°
Efficiency	94 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
C16876_DAISSY-7X1-SHD-WHT




Light distribution files

OPTICAL RESULTS (SIMULATED):

OSRAM
Opto Semiconductors

LED Duris E 2835
FWHM / FWTM 76.0° / 86.0°
Efficiency 94 %
Peak intensity 0.7 cd/lm
LEDs/each optic 2
Light colour/type White

Required components:
C16876_DAISSY-7X1-SHD-WHT




Light distribution files

OSRAM
Opto Semiconductors

LED Duris E 2835
FWHM / FWTM 76.0° / 88.0°
Efficiency 93 %
Peak intensity 0.7 cd/lm
LEDs/each optic 4
Light colour/type White

Required components:
C17225_DAISSY-7X1-SHD-WHT-MATT




Light distribution files

OSRAM
Opto Semiconductors

LED Duris E 2835
FWHM / FWTM 76.0° / 86.0°
Efficiency 89 %
Peak intensity 0.7 cd/lm
LEDs/each optic 2
Light colour/type White

Required components:
C16872_DAISSY-7X1-SHD



Light distribution files


OPTICAL RESULTS (SIMULATED):

OSRAM
Opto Semiconductors

LED Duris E 2835
FWHM / FWTM 76.0° / 89.0°
Efficiency 89 %
Peak intensity 0.7 cd/lm
LEDs/each optic 4
Light colour/type White

Required components:

C17051_DAISSY-7X1-SHD-MATT




Light distribution files

OSRAM
Opto Semiconductors

LED OSLOM PURE 1010
FWHM / FWTM 76.0° / 88.0°
Efficiency 83 %
Peak intensity 0.6 cd/lm
LEDs/each optic 8
Light colour/type White

Required components:

C16872_DAISSY-7X1-SHD




Light distribution files

OSRAM
Opto Semiconductors

LED OSLOM PURE 1010
FWHM / FWTM 76.0° / 87.0°
Efficiency 83 %
Peak intensity 0.7 cd/lm
LEDs/each optic 8
Light colour/type White

Required components:

C17051_DAISSY-7X1-SHD-MATT




Light distribution files

OPTICAL RESULTS (SIMULATED):

SAMSUNG

LED LH181B
FWHM / FWTM 76.0° / 85.0°
Efficiency 93 %
Peak intensity 0.7 cd/lm
LEDs/each optic 2
Light colour/type White

Required components:
C18167_DAISSY-7X1-SHD-MET




Light distribution files

SAMSUNG

LED LH231B
FWHM / FWTM 74.0° / 86.0°
Efficiency 91 %
Peak intensity 0.7 cd/lm
LEDs/each optic 4
Light colour/type White

Required components:
C17225_DAISSY-7X1-SHD-WHT-MATT




Light distribution files

SAMSUNG

LED LH231B
FWHM / FWTM 75.0° / 86.0°
Efficiency 91 %
Peak intensity 0.7 cd/lm
LEDs/each optic 2
Light colour/type White

Required components:
C17225_DAISSY-7X1-SHD-WHT-MATT




Light distribution files

OPTICAL RESULTS (SIMULATED):

SAMSUNG


LED LM28xB Series
FWHM / FWTM 71.0° / 87.0°
Efficiency 90 %
Peak intensity 0.9 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
C19312_DAISSY-7X1-SHD3



Light distribution files

SAMSUNG


LED LM28xB Series
FWHM / FWTM 77.0° / 90.0°
Efficiency 84 %
Peak intensity 0.7 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
C16872_DAISSY-7X1-SHD



Light distribution files

SAMSUNG

LED LM28xB Series
FWHM / FWTM 63.0° / 86.0°
Efficiency 98 %
Peak intensity 1.1 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
C19314_DAISSY-7X1-SHD3-WHT




Light distribution files

OPTICAL RESULTS (SIMULATED):

SAMSUNG


LED LM28xB Series
FWHM / FWTM 72.0° / 87.0°
Efficiency 96 %
Peak intensity 0.9 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
C19313_DAISSY-7X1-SHD3-MATT



Light distribution files

SAMSUNG


LED LM28xB Series
FWHM / FWTM 65.0° / 86.0°
Efficiency 96 %
Peak intensity 1.1 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
C19641_DAISSY-7X1-SHD3-MET



Light distribution files

SAMSUNG

LED LM301B
FWHM / FWTM 76.0° / 90.0°
Efficiency 89 %
Peak intensity 0.7 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:
C16872_DAISSY-7X1-SHD




Light distribution files

OPTICAL RESULTS (SIMULATED):

SAMSUNG


LED LM301D
 FWHM / FWTM 74.0° / 88.0°
 Efficiency 93 %
 Peak intensity 0.7 cd/lm
 LEDs/each optic 4
 Light colour/type White
 Required components:
 C17225_DAISSY-7X1-SHD-WHT-MATT



Light distribution files




LED SEOUL DC 3030C
 FWHM / FWTM 77.0° / 90.0°
 Efficiency 89 %
 Peak intensity 0.7 cd/lm
 LEDs/each optic 4
 Light colour/type White
 Required components:
 C16872_DAISSY-7X1-SHD



Light distribution files




LED SEOUL DC 3528
 FWHM / FWTM 78.0° / 86.0°
 Efficiency 89 %
 Peak intensity 0.7 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 C16872_DAISSY-7X1-SHD



Light distribution files

OPTICAL RESULTS (SIMULATED):



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 7
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Poznan, Poland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)