DAISY-7X1-W-D

~50° wide beam. Variant with diffused lenses. Choose SHD with no lips or SHD2 with narrow lips and square openings. SHD3 with narrow lips and round openings.

SPECIFICATION:

Dimensions	279.5 x 39.6
Height	20.3 mm
Fastening	pin, screw, clips
ROHS compliant	yes

MATERIALS:

Component	Type	Material	Colour	Finish	Length (mm)
DAISY-7X1-W-D	Linear lens	PMMA	milky		
DAISY-7X1-SHD2-MET-MATT	Shade	PC-ABS	metal	matt	
DAISY-7X1-SHD2-MET	Shade	PC	metal	gloss	
DAISY-7X1-SHD2-MATT-WHT	Shade	PC	white	matt	
DAISY-7X1-SHD2-WHT	Shade	PC	white	gloss	
DAISY-7X1-SHD2-MATT	Shade	PC-ABS	black	matt	
DAISY-7X1-SHD2	Shade	PC	black	gloss	
DAISY-7X1-SHD3-MATT-GLD	Shade	PC	gold	matt	
DAISY-7X1-SHD3-MATT-RED	Shade	PC	red	matt	
DAISY-7X1-SHD3-MATT-GR	Shade	PC	grey	matt	
DAISY-7X1-SHD-MATT-GLD	Shade	PC	gold	matt	
DAISY-7X1-SHD-MATT-GR	Shade	PC	grey	matt	
DAISY-7X1-SHD-MATT-RED	Shade	PC	red	matt	
DAISY-7X1-SHD3-MET-MATT	Shade	PC	metal	matt	
DAISY-7X1-SHD3-MET	Shade	PC	metal	gloss	
DAISY-7X1-SHD3-WHT-MATT	Shade	PC	white	matt	
DAISY-7X1-SHD3-WHT	Shade	PC	white	gloss	

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

DAISY-7X1-SHD-MATT	Shade	PC	black	matt
DAISY-7X1-SHD-MET-MATT	Shade	PC	metal	matt
DAISY-7X1-SHD-MET	Shade	PC	metal	gloss
DAISY-7X1-SHD-WHT-MATT	Shade	PC	white	matt
DAISY-7X1-SHD-MATT	Shade	PC	black	matt
DAISY-7X1-SHD-WHT	Shade	PC	white	gloss
DAISY-7X1-SHD	Shade	PC	black	gloss

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

ORDERING INFORMATION:

Quantities for one set:

Linear lens	1
Shade	1

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

Component		Qty in box	MOQ	MPQ	Box weight (kg)
C17362_DAISY-7X1-W-D » Box size: 400 x 300 x 300 mm	Linear lens	312	312	24	6.3
C16876_DAISY-7X1-SHD-WHT » Box size: 595 x 360 x 230 mm	Shade	156	312	24	7.6
L20015_DAISY-7X1-SHD2-MET-MATT » Box size: 595 x 360 x 230 mm	Shade	156	312	24	6.6
C19852_DAISY-7X1-SHD-MATT-GLD » Box size: 595 x 360 x 230 mm	Shade	156	312	24	7.1
C18409_DAISY-7X1-SHD-MET-MATT » Box size: 595 x 360 x 230 mm	Shade	156	312	24	7.0
L20011_DAISY-7X1-SHD2-MATT » Box size: 595 x 360 x 230 mm	Shade	156	312	24	6.7
C19641_DAISY-7X1-SHD3-MET » Box size: 595 x 360 x 230 mm	Shade	156	312	24	6.1
C17051_DAISY-7X1-SHD-MATT » Box size: 595 x 360 x 230 mm	Shade	156	312	24	7.3
C19853_DAISY-7X1-SHD3-MATT-GR » Box size: 595 x 360 x 230 mm	Shade	156	312	24	7.1
C19312_DAISY-7X1-SHD3 » Box size: 595 x 360 x 230 mm	Shade	156	312	24	6.1
L20012_DAISY-7X1-SHD2-WHT » Box size: 595 x 360 x 230 mm	Shade	156	312	24	7.2
C19642_DAISY-7X1-SHD3-MET-MATT » Box size: 595 x 360 x 230 mm	Shade	156	312	24	5.7
C17225_DAISY-7X1-SHD-WHT-MATT » Box size: 595 x 360 x 230 mm	Shade	156	312	24	7.6
C19854_DAISY-7X1-SHD3-MATT-RED » Box size: 595 x 360 x 230 mm	Shade	156	312	24	6.2
C19313_DAISY-7X1-SHD3-MATT » Box size: 595 x 360 x 230 mm	Shade	156	312	24	5.8
L20013_DAISY-7X1-SHD2-MATT-WHT » Box size: 595 x 360 x 230 mm	Shade	156	312	24	7.1
C19763_DAISY-7X1-SHD-MATT-RED » Box size: 595 x 360 x 230 mm	Shade	156	312	24	7.1
C19855_DAISY-7X1-SHD3-MATT-GLD » Box size: 595 x 360 x 230 mm	Shade	156	312	24	6.2
C19314_DAISY-7X1-SHD3-WHT » Box size: 595 x 360 x 230 mm	Shade	156	312	24	6.3

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

L20014_DAISY-7X1-SHD2-MET » Box size: 595 x 360 x 230 mm	Shade	156	312	24	7.0
C19764_DAISY-7X1-SHD-MATT-GR » Box size: 595 x 360 x 230 mm	Shade	156	312	24	5.7
C18167_DAISY-7X1-SHD-MET » Box size: 595 x 360 x 230 mm	Shade	156	312	24	7.0
L20010_DAISY-7X1-SHD2 » Box size: 595 x 360 x 230 mm	Shade	156	312	24	6.9
C19315_DAISY-7X1-SHD3-WHT-MATT » Box size: 595 x 360 x 230 mm	Shade	156	312	24	6.2

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

DATE 23.10.2024





Top view
Scale: 3:4

CN17366_DAISY-7X1-W-D

COMPONENTS

INDEX	QTY.	PART	TYPE	MATERIAL	COLOR / COATING
1	1	C17362_DAISY-7X1-W-D	LENS	PMMA	DF21 Diffusive
2	1	SHD	SHADE		
		C16872_DAISY-7X1-SHD	SHADE	PC/ABS	BLACK/GLOSS
		C17051_DAISY-7X1-SHD-MATT	SHADE	PC/ABS	BLACK/MATT
		C16876_DAISY-7X1-SHD-WHT	SHADE	PC	WHITE/GLOSS
		C17225_DAISY-7X1-SHD-WHT-MATT	SHADE	PC	WHITE/MATT
		C18167_DAISY-7X1-SHD-MET	SHADE	PC	METAL/GLOSS
		C18409_DAISY-7X1-SHD-MET-MATT	SHADE	PC	METAL/MATT
		C19763_DAISY-7X1-SHD-MATT-RED	SHADE	PC	RED/MATT
		C19764_DAISY-7X1-SHD-MATT-GR	SHADE	PC	GREY/MATT
		C19852_DAISY-7X1-SHD-MATT-GLD	SHADE	PC	GOLD/MATT

Notes

- PCB or heatsink level.
- LED location
- Ensure LED fitting from a product specific 3D model available from www.ledil.com
- For more details about installation please see LEDiL Installation Guide on www.ledil.com

MECHANICAL DRAWING

PRODUCT DAISY-7X1

Plastic moulding general tolerances according to DIN 16901-130 and applies if not otherwise shown in the drawing. Silicone moulding general tolerances according to ISO 3302-1 Class M3 and applies if not otherwise shown in the drawing.

FIRST ANGLE PROJECTION:

This drawing is the property of LEDiL Oy. It may not be copied or otherwise distributed without prior written permission from LEDiL Oy.

SCALE 1:1 | WEIGHT - | A3 | SHEET 1/3

DATE 23.10.2024





Top view
Scale: 3:4



CN17366_DAISY-7X1-W-D

COMPONENTS

INDEX	QTY.	PART	TYPE	MATERIAL	COLOR / COATING
1	1	C17362_DAISY-7X1-W-D	LENS	PMMA	DF21 Diffusive
2	1	SHD3	SHADE		
		C19312_DAISY-7X1-SHD3	SHADE	PC	BLACK/GLOSS
		C19313_DAISY-7X1-SHD3-MATT	SHADE	PC/ABS	BLACK/MATT
		C19314_DAISY-7X1-SHD3-WHT	SHADE	PC	WHITE/GLOSS
		C19315_DAISY-7X1-SHD3-WHT-MATT	SHADE	PC	WHITE/MATT
		C19641_DAISY-7X1-SHD3-MET	SHADE	PC	METAL/GLOSS
		C19642_DAISY-7X1-SHD3-MET-MATT	SHADE	PC/ABS	METAL/MATT
		C19853_DAISY-7X1-SHD3-MATT-GR	SHADE	PC	GREY/MATT
		C19854_DAISY-7X1-SHD3-MATT-RED	SHADE	PC	RED/MATT
		C19855_DAISY-7X1-SHD3-MATT-GLD	SHADE	PC	GOLD/MATT

Notes

- PCB or heatsink level.
- LED location
- Ensure LED fitting from a product specific 3D model available from www.ledil.com
- For more details about installation please see LEDiL Installation Guide on www.ledil.com

MECHANICAL DRAWING

PRODUCT DAISY-7X1

Plastic moulding general tolerances according to DIN 16901-130 and applies if not otherwise shown in the drawing. Silicone moulding general tolerances according to ISO 3302-1 Class M3 and applies if not otherwise shown in the drawing.

FIRST ANGLE PROJECTION:

This drawing is the property of LEDiL Oy. It may not be copied or otherwise distributed without prior written permission from LEDiL Oy.

SCALE 1:1 | WEIGHT - | A3 | SHEET 2/3

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.



See also our general installation guide: www.ledil.com/installation_guide

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

AUDAX ELECTRONICS

LED	LIGHT ENGINE DAISY 28 LEDs 277.5mm x 20mm
FWHM / FWTM	65.0° / 92.0°
Efficiency	90 %
Peak intensity	0.8 cd/lm
LEDs/each optic	4
Light colour/type	White

Required components:

C16876_DAISY-7X1-SHD-WHT



Light distribution files

AUDAX ELECTRONICS

LED	LIGHT ENGINE DAISY 28 LEDs 277.5mm x 20mm
FWHM / FWTM	65.0° / 92.0°
Efficiency	89 %
Peak intensity	0.8 cd/lm
LEDs/each optic	4
Light colour/type	White

Required components:

C17225_DAISY-7X1-SHD-WHT-MATT



Light distribution files

AUDAX ELECTRONICS

LED	LIGHT ENGINE DAISY 28 LEDs 277.5mm x 20mm
FWHM / FWTM	64.0° / 90.0°
Efficiency	88 %
Peak intensity	0.8 cd/lm
LEDs/each optic	4
Light colour/type	White

Required components:

C17533_DAISY-7X1-SHD-MET-MATT





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

AUDAX ELECTRONICS

LED	LIGHT ENGINE DAISY 28 LEDs 277.5mm x 20mm
FWHM / FWTM	64.0° / 89.0°
Efficiency	78 %
Peak intensity	0.8 cd/lm
LEDs/each optic	4
Light colour/type	White

Required components:
C16872_DAISY-7X1-SHD



Light distribution files

AUDAX ELECTRONICS

LED	LIGHT ENGINE DAISY 28 LEDs 277.5mm x 20mm
FWHM / FWTM	63.0° / 88.0°
Efficiency	77 %
Peak intensity	0.8 cd/lm
LEDs/each optic	4
Light colour/type	White

Required components:
C17051_DAISY-7X1-SHD-MATT



Light distribution files

AUDAX ELECTRONICS

LED	LIGHT ENGINE DAISY 28 LEDs 277.5mm x 20mm
FWHM / FWTM	64.0° / 90.0°
Efficiency	90 %
Peak intensity	0.8 cd/lm
LEDs/each optic	4
Light colour/type	White

Required components:
C18167_DAISY-7X1-SHD-MET



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

inventronics

LED	PL-LIN-2000 280x24mm
FWHM / FWTM	64.0° / 89.0°
Efficiency	76 %
Peak intensity	0.7 cd/lm
LEDs/each optic	4
Light colour/type	White

Required components:
C17051_DAISY-7X1-SHD-MATT



Light distribution files

LUMILEDS

LED	LUXEON 2835 Line
FWHM / FWTM	64.0° / 90.0°
Efficiency	90 %
Peak intensity	0.8 cd/lm
LEDs/each optic	4
Light colour/type	White

Required components:
C17532_DAISY-7X1-SHD-MET



Light distribution files

LUMILEDS

LED	LUXEON 2835 Line
FWHM / FWTM	65.0° / 93.0°
Efficiency	90 %
Peak intensity	0.8 cd/lm
LEDs/each optic	4
Light colour/type	White

Required components:
C16876_DAISY-7X1-SHD-WHT



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

LUMILEDS

LED	LUXEON 2835 Line
FWHM / FWTM	65.0° / 92.0°
Efficiency	89 %
Peak intensity	0.8 cd/lm
LEDs/each optic	4
Light colour/type	White

Required components:
C17225_DAISY-7X1-SHD-WHT-MATT



Light distribution files

LUMILEDS

LED	LUXEON 2835 Line
FWHM / FWTM	64.0° / 91.0°
Efficiency	88 %
Peak intensity	0.8 cd/lm
LEDs/each optic	4
Light colour/type	White

Required components:
C17533_DAISY-7X1-SHD-MET-MATT



Light distribution files

LUMILEDS

LED	LUXEON 2835 Line
FWHM / FWTM	64.0° / 89.0°
Efficiency	78 %
Peak intensity	0.8 cd/lm
LEDs/each optic	4
Light colour/type	White

Required components:
C16872_DAISY-7X1-SHD

Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

LUMILEDS

LED	LUXEON 2835 Line
FWHM / FWTM	63.0° / 88.0°
Efficiency	77 %
Peak intensity	0.8 cd/lm
LEDs/each optic	4
Light colour/type	White

Required components:
C17051_DAISY-7X1-SHD-MATT



Light distribution files

MST Your solutions

LED	LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1
FWHM / FWTM	64.0° / 91.0°
Efficiency	88 %
Peak intensity	0.8 cd/lm
LEDs/each optic	4
Light colour/type	White

Required components:
C18167_DAISY-7X1-SHD-MET



Light distribution files

MST Your solutions

LED	LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1
FWHM / FWTM	64.0° / 89.0°
Efficiency	77 %
Peak intensity	0.7 cd/lm
LEDs/each optic	4
Light colour/type	White

Required components:
C16872_DAISY-7X1-SHD



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

MST Your solutions

LED	LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1
FWHM / FWTM	65.0° / 93.0°
Efficiency	88 %
Peak intensity	0.8 cd/lm
LEDs/each optic	4
Light colour/type	White

Required components:
C17225_DAISY-7X1-SHD-WHT-MATT



Light distribution files

MST Your solutions

LED	LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1
FWHM / FWTM	64.0° / 92.0°
Efficiency	87 %
Peak intensity	0.8 cd/lm
LEDs/each optic	4
Light colour/type	White

Required components:
C17533_DAISY-7X1-SHD-MET-MATT



Light distribution files

MST Your solutions

LED	LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1
FWHM / FWTM	65.0° / 93.0°
Efficiency	88 %
Peak intensity	0.8 cd/lm
LEDs/each optic	4
Light colour/type	White

Required components:
C16876_DAISY-7X1-SHD-WHT



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

MST Your solutions

LED	LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1
FWHM / FWTM	64.0° / 89.0°
Efficiency	76 %
Peak intensity	0.7 cd/lm
LEDs/each optic	4
Light colour/type	White

Required components:
C17051_DAISY-7X1-SHD-MATT



Light distribution files

MST Your solutions

LED	LinLED 280x28mm 1600lm 840 4C 21V DAISY 7x1(ZT25)
FWHM / FWTM	56.0° / 81.0°
Efficiency	81 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
C16872_DAISY-7X1-SHD





Light distribution files

MST Your solutions

LED	LinLED 280x28mm 2x550lm 827-865 2x2C 42V DAISY-7X
FWHM / FWTM	66.0° / 94.0°
Efficiency	89 %
Peak intensity	0.7 cd/lm
LEDs/each optic	4
Light colour/type	Tunable White

Required components:
C16876_DAISY-7X1-SHD-WHT





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

MST Your solutions

LED	LinLED 280x28mm 2x550lm 827-865 2x2C 42V DAISY-7X
FWHM / FWTM	66.0° / 94.0°
Efficiency	89 %
Peak intensity	0.7 cd/lm
LEDs/each optic	4
Light colour/type	Tunable White

Required components:
C17225_DAISY-7X1-SHD-WHT-MATT





Light distribution files

MST Your solutions

LED	LinLED 280x28mm 2x550lm 827-865 2x2C 42V DAISY-7X
FWHM / FWTM	65.0° / 92.0°
Efficiency	87 %
Peak intensity	0.8 cd/lm
LEDs/each optic	4
Light colour/type	Tunable White

Required components:
C17533_DAISY-7X1-SHD-MET-MATT





Light distribution files

MST Your solutions

LED	LinLED 280x28mm 2x550lm 827-865 2x2C 42V DAISY-7X
FWHM / FWTM	65.0° / 90.0°
Efficiency	77 %
Peak intensity	0.7 cd/lm
LEDs/each optic	4
Light colour/type	Tunable White

Required components:
C16872_DAISY-7X1-SHD





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

MST Your solutions

LED	LinLED 280x28mm 2x550lm 827-865 2x2C 42V DAISY-7X
FWHM / FWTM	65.0° / 90.0°
Efficiency	76 %
Peak intensity	0.7 cd/lm
LEDs/each optic	4
Light colour/type	Tunable White

Required components:
C17051_DAISY-7X1-SHD-MATT





Light distribution files

MST Your solutions

LED	LinLED 280x28mm 2x550lm 827-865 2x2C 42V DAISY-7X
FWHM / FWTM	65.0° / 91.0°
Efficiency	89 %
Peak intensity	0.8 cd/lm
LEDs/each optic	4
Light colour/type	Tunable White

Required components:
C18167_DAISY-7X1-SHD-MET



Light distribution files

NICHIA

LED	NF2W757G-MT (Tunable White)
FWHM / FWTM	61.0° / 84.0°
Efficiency	82 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour/type	Tunable White

Required components:
C16872_DAISY-7X1-SHD





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

NICHIA

LED	NF2W757G-MT (Tunable White)
FWHM / FWTM	62.0° / 86.0°
Efficiency	93 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour/type	Tunable White

Required components:
C16876_DAISY-7X1-SHD-WHT



Light distribution files

OSRAM
Opto Semiconductors

LED	OSCONIQ E 2835
FWHM / FWTM	64.0° / 89.0°
Efficiency	76 %
Peak intensity	0.7 cd/lm
LEDs/each optic	4
Light colour/type	White

Required components:
C17051_DAISY-7X1-SHD-MATT



Light distribution files

SAMSUNG

LED	LM28xB Series
FWHM / FWTM	61.0° / 85.0°
Efficiency	82 %
Peak intensity	0.9 cd/lm
LEDs/each optic	2
Light colour/type	White

Required components:
C16872_DAISY-7X1-SHD



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

SAMSUNG

LED	LM28xB Series
FWHM / FWTM	62.0° / 88.0°
Efficiency	92 %
Peak intensity	0.9 cd/lm
LEDs/each optic	2
Light colour/type	White

Required components:
C16876_DAISY-7X1-SHD-WHT



Light distribution files

SAMSUNG

LED	LM28xB Series
FWHM / FWTM	60.0° / 84.0°
Efficiency	77 %
Peak intensity	0.8 cd/lm
LEDs/each optic	2
Light colour/type	White

Required components:
C17051_DAISY-7X1-SHD-MATT



Light distribution files

SEITEC Elektronik GmbH

LED	LED-St-L28W2c4-xxx-C015-55 (DAISY-7x1)
FWHM / FWTM	64.0° / 89.0°
Efficiency	77 %
Peak intensity	0.8 cd/lm
LEDs/each optic	4
Light colour/type	White

Required components:
C17051_DAISY-7X1-SHD-MATT



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

LED	LED-St-L28W2c4-xxx-C015-55 (DAISY-7x1)
FWHM / FWTM	64.0° / 90.0°
Efficiency	91 %
Peak intensity	0.8 cd/lm
LEDs/each optic	4
Light colour/type	White

Required components:
C18167_DAISY-7X1-SHD-MET



Light distribution files

LED	LED-St-L28W2c4-xxx-C015-55 (DAISY-7x1)
FWHM / FWTM	63.0° / 91.0°
Efficiency	90 %
Peak intensity	0.8 cd/lm
LEDs/each optic	4
Light colour/type	White

Required components:
C17533_DAISY-7X1-SHD-MET-MATT



Light distribution files

LED	LED-St-L28W2c4-xxx-C015-55 (DAISY-7x1)
FWHM / FWTM	65.0° / 93.0°
Efficiency	90 %
Peak intensity	0.8 cd/lm
LEDs/each optic	4
Light colour/type	White

Required components:
C16876_DAISY-7X1-SHD-WHT



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

LED	LED-St-L28W2c4-xxx-C015-55 (DAISY-7x1)
FWHM / FWTM	65.0° / 93.0°
Efficiency	91 %
Peak intensity	0.8 cd/lm
LEDs/each optic	4
Light colour/type	White

Required components:
C17225_DAISY-7X1-SHD-WHT-MATT





Light distribution files

LED	LED-St-L28W2c4-xxx-C015-55 (DAISY-7x1)
FWHM / FWTM	64.0° / 89.0°
Efficiency	78 %
Peak intensity	0.7 cd/lm
LEDs/each optic	4
Light colour/type	White

Required components:
C16872_DAISY-7X1-SHD



Light distribution files

LED	PassivePAQ-L-1F35-SSA3-2.7K-840-3-DC
FWHM / FWTM	70.0° / 100.0°
Efficiency	87 %
Peak intensity	0.6 cd/lm
LEDs/each optic	4
Light colour/type	White

Required components:
C16876_DAISY-7X1-SHD-WHT





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

TEPCOMP group

LED	PassivePAQ-L-1F35-SSA3-2.7K-840-3-DC
FWHM / FWTM	68.0° / 94.0°
Efficiency	71 %
Peak intensity	0.6 cd/lm
LEDs/each optic	4
Light colour/type	White

Required components:
C17051_DAISY-7X1-SHD-MATT



Light distribution files

TEPCOMP group

LED	PassivePAQ-L-1F35-SSA3-2.7K-840-3-DC
FWHM / FWTM	68.0° / 93.0°
Efficiency	71 %
Peak intensity	0.6 cd/lm
LEDs/each optic	4
Light colour/type	White

Required components:
C16872_DAISY-7X1-SHD



Light distribution files

TEPCOMP group

LED	PassivePAQ-L-1F35-SSA3-2.7K-840-3-DC
FWHM / FWTM	70.0° / 100.0°
Efficiency	87 %
Peak intensity	0.6 cd/lm
LEDs/each optic	4
Light colour/type	White

Required components:
C17225_DAISY-7X1-SHD-WHT-MATT



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

TRIDONIC

LED	LLE 24x280mm 750lm 8x0 LVD ADV1
FWHM / FWTM	65.0° / 90.0°
Efficiency	76 %
Peak intensity	0.7 cd/lm
LEDs/each optic	4
Light colour/type	White

Required components:
C17051_DAISY-7X1-SHD-MATT



Light distribution files

TRIDONIC

LED	LLE 24x280mm 750lm 8x0 LVD ADV1
FWHM / FWTM	65.0° / 90.0°
Efficiency	76 %
Peak intensity	0.7 cd/lm
LEDs/each optic	4
Light colour/type	White

Required components:
C16872_DAISY-7X1-SHD



Light distribution files

TRIDONIC

LED	LLE 24x280mm 750lm 8x0 LVD ADV1
FWHM / FWTM	66.0° / 95.0°
Efficiency	89 %
Peak intensity	0.7 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
C17225_DAISY-7X1-SHD-WHT-MATT



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

TRIDONIC

LED	LLE 24x280mm 750lm 8x0 LVD ADV1
FWHM / FWTM	66.0° / 95.0°
Efficiency	89 %
Peak intensity	0.7 cd/lm
LEDs/each optic	4
Light colour/type	White
Required components:	
C16876_DAISY-7X1-SHD-WHT	



Light distribution files

LEDiL®

LED	BLX-LN-560-24-C2-2400 (Daisy-7x1)
FWHM / FWTM	64.0° / 93.0°
Efficiency	89 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
C16876_DAISY-7X1-SHD-WHT	



Light distribution files

LEDiL®

LED	BLX-LN-560-24-C2-2400 (Daisy-7x1)
FWHM / FWTM	64.0° / 89.0°
Efficiency	76 %
Peak intensity	0.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
C16872_DAISY-7X1-SHD	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

bridgelux

LED	SMD 3838 RGBW 3V
FWHM / FWTM	56.0° / 86.0°
Efficiency	80 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour/type	RGBW
Required components:	
C16872_DAISY-7X1-SHD	



Light distribution files

CREE LEDs

LED	J Series 2835
FWHM / FWTM	62.0° / 90.0°
Efficiency	78 %
Peak intensity	0.8 cd/lm
LEDs/each optic	4
Light colour/type	White
Required components:	
C16872_DAISY-7X1-SHD	



Light distribution files

MST Your solutions

LED	LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1
FWHM / FWTM	62.0° / 86.0°
Efficiency	74 %
Peak intensity	0.8 cd/lm
LEDs/each optic	4
Light colour/type	White
Required components:	
C17051_DAISY-7X1-SHD-MATT	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

MST Your solutions

LED	LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1
FWHM / FWTM	62.0° / 86.0°
Efficiency	86 %
Peak intensity	0.9 cd/lm
LEDs/each optic	4
Light colour/type	White
Required components:	
C16876_DAISY-7X1-SHD-WHT	



Light distribution files

MST Your solutions

LED	LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1
FWHM / FWTM	62.0° / 86.0°
Efficiency	90 %
Peak intensity	1 cd/lm
LEDs/each optic	4
Light colour/type	White
Required components:	
C17533_DAISY-7X1-SHD-MET-MATT	



Light distribution files

MST Your solutions

LED	LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1
FWHM / FWTM	62.0° / 85.0°
Efficiency	74 %
Peak intensity	0.8 cd/lm
LEDs/each optic	4
Light colour/type	White
Required components:	
C16872_DAISY-7X1-SHD	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

MST Your solutions

LED	LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1
FWHM / FWTM	62.0° / 86.0°
Efficiency	86 %
Peak intensity	0.9 cd/lm
LEDs/each optic	4
Light colour/type	White
Required components:	
C17225_DAISY-7X1-SHD-WHT-MATT	



Light distribution files

MST Your solutions

LED	LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1
FWHM / FWTM	62.0° / 86.0°
Efficiency	90 %
Peak intensity	0.9 cd/lm
LEDs/each optic	4
Light colour/type	White
Required components:	
C18167_DAISY-7X1-SHD-MET	



Light distribution files

OSRAM Opto Semiconductors

LED	Duris E 2835
FWHM / FWTM	62.0° / 90.0°
Efficiency	83 %
Peak intensity	0.8 cd/lm
LEDs/each optic	4
Light colour/type	White
Required components:	
C17051_DAISY-7X1-SHD-MATT	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

OSRAM
Opto Semiconductors

LED	Duris E 2835
FWHM / FWTM	61.0° / 91.0°
Efficiency	88 %
Peak intensity	0.9 cd/lm
LEDs/each optic	4
Light colour/type	White
Required components:	
C17225_DAISY-7X1-SHD-WHT-MATT	



Light distribution files

OSRAM
Opto Semiconductors

LED	OSLON PURE 1010
FWHM / FWTM	50.0° / 76.0°
Efficiency	86 %
Peak intensity	1.3 cd/lm
LEDs/each optic	4
Light colour/type	White
Required components:	
C17225_DAISY-7X1-SHD-WHT-MATT	



Light distribution files

SAMSUNG

LED	LH231B
FWHM / FWTM	56.0° / 84.0°
Efficiency	75 %
Peak intensity	0.9 cd/lm
LEDs/each optic	2
Light colour/type	White
Required components:	
C17225_DAISY-7X1-SHD-WHT-MATT	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

SAMSUNG

LED	LM101B
FWHM / FWTM	54.0° / 78.0°
Efficiency	86 %
Peak intensity	1.1 cd/lm
LEDs/each optic	4
Light colour/type	White
Required components:	
C17225_DAISY-7X1-SHD-WHT-MATT	



Light distribution files

SAMSUNG

LED	LM101B
FWHM / FWTM	58.0° / 82.0°
Efficiency	88 %
Peak intensity	1 cd/lm
LEDs/each optic	4
Light colour/type	White
Required components:	
C18167_DAISY-7X1-SHD-MET	



Light distribution files

SAMSUNG

LED	LM28xB Series
FWHM / FWTM	60.0° / 84.0°
Efficiency	87 %
Peak intensity	1 cd/lm
LEDs/each optic	4
Light colour/type	White
Required components:	
C19641_DAISY-7X1-SHD3-MET	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

SAMSUNG

LED	LM28xB Series
FWHM / FWTM	55.0° / 80.0°
Efficiency	89 %
Peak intensity	1.1 cd/lm
LEDs/each optic	2
Light colour/type	White
Required components:	
C19641_DAISY-7X1-SHD3-MET	



Light distribution files

SAMSUNG

LED	LM301Z Plus
FWHM / FWTM	60.0° / 86.0°
Efficiency	86 %
Peak intensity	0.9 cd/lm
LEDs/each optic	4
Light colour/type	White
Required components:	
C17225_DAISY-7X1-SHD-WHT-MATT	



Light distribution files

SAMSUNG

LED	LM301Z Plus
FWHM / FWTM	60.0° / 86.0°
Efficiency	75 %
Peak intensity	0.8 cd/lm
LEDs/each optic	4
Light colour/type	White
Required components:	
C17051_DAISY-7X1-SHD-MATT	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

SAMSUNG

LED	LM301Z Plus
FWHM / FWTM	62.0° / 86.0°
Efficiency	88 %
Peak intensity	0.9 cd/lm
LEDs/each optic	4
Light colour/type	White
Required components:	
C18167_DAISY-7X1-SHD-MET	



Light distribution files

SEOUL SEMICONDUCTOR

LED	SEOUL DC 3030C
FWHM / FWTM	62.0° / 88.0°
Efficiency	80 %
Peak intensity	0.8 cd/lm
LEDs/each optic	4
Light colour/type	White
Required components:	
C16872_DAISY-7X1-SHD	



Light distribution files

SEOUL SEMICONDUCTOR

LED	SEOUL DC 3528
FWHM / FWTM	59.0° / 84.0°
Efficiency	76 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
C16872_DAISY-7X1-SHD	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

TRIDONIC

LED	LLE 24x280mm 750lm 8x0 LVD ADV1
FWHM / FWTM	62.0° / 89.0°
Efficiency	93 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
C17225_DAISY-7X1-SHD-WHT-MATT	



Light distribution files

TRIDONIC

LED	LLE 24x280mm 750lm 8x0 LVD ADV1
FWHM / FWTM	62.0° / 88.0°
Efficiency	88 %
Peak intensity	0.9 cd/lm
LEDs/each optic	4
Light colour/type	White
Required components:	
C17533_DAISY-7X1-SHD-MET-MATT	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy
Joensuunkatu 7
FI-24100 SALO
Finland

LEDiL Inc.
228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.
405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support
www.ledil.com/where_to_buy

Shipping locations
Poznan, Poland
Hong Kong, China

Distribution Partners
www.ledil.com/where_to_buy

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.