





未注公差/General tolerances(mm)														 0.1/10  2°
0 ~ 3	>3 ~ 6	>6 ~ 10	>10 ~ 18	>18 ~ 30	>30 ~ 50	>50 ~ 80	>80 ~ 120	>120 ~ 180	>180 ~ 250	>250 ~ 315	>315 ~ 400	>400 ~ 500	>500	
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	



4	Pin header	Copper alloy	Sn plated
3	Housing	PA66	UL94V-0
2	Spring	Stainless steel	/
1	Cover	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	300/15	/	300/10
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	/	450/17	/
工频耐压/Withstanding Voltage(V/Min)	AC2500		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm²)	28~12/ 0.2~2.5		
间距/Pitch(mm)/线数范围/Poles	5.0/N~01~24P		
剥线长度/Stripping length(mm)	5~6		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

			MATERIAL:		SURFACE/COLOR:							
APPD: 兰春华			MAT NO./REV: / 00		MAT STATUS: 批量							
CHKD: 陈招			NAME DG245-5.0-XXP-1Y-00Z (H)									
DRFT: 龚徐涛												
			DRAWING NO. 200102971		TYPE CUSTOMER DRAWING		DRAWING STATUS 已发布		SCALE 2:1		SHEET 1/1	

00		原PDM无外部2D, 新出外部2D 00版	龚徐涛	2022.08.15
REV	ECN	DESCRIPTION	DRFT	DATE