

HOW DER

DESCRIPTION	DATE
RELEASED	APR/13/06

SPECIFICATIONS

BARRIER MATERIAL: THERMOPLASTIC (UL 94V-0) GREEN

TERMINALS: TIN PLATED BRASS

SCREWS:ZINC PLATED STEEL

WIRE RANGE AWG: 22-16 STR

RATING: 10 AMPERES. 250 VAC

INSULATION WITHSTANDS VOLTAGE AC 2000V




INSULATION RESISTANCE 500 OR MORE AT DC 500V

FEATURES

SUPPLY 2P 3P CAN BE DOVETAILED TOGETHER TO MAKE ANY LENGTH & DIFFERENT COMBINATIONS

Part Number: TS-501- P

Pole Size 2~26P



POLE	2	3	4	5	6	7	8	9	10	11	12	13	14	15
A	10.5	15.5	20.5	25.5	30.5	35.5	40.5	45.5	50.5	55.5	60.5	65.5	70.5	75.5
B	5	10	15	20	25	30	35	40	45	50	55	60	65	70
	16	17	18	19	20	21	22	23	24	25	26			
A	80.5	85.5	90.5	95.5	100.5	105.5	110.5	115.5	120.5	125.5	130.5			
B	75	80	85	90	95	100	105	110	115	120	125			

CO/Name	HOW DER ELECTRIC CO.,LTD	Tolerance Unless Otherwise Specified	Designed	Drawing	Reviewed	Approved	Approvered	DrawingNo	TB-9503001
P/Name	Euro type terminal block	.X ~ ±0.3						Pitch	5.0 mm
						Date			
						Unit		mm	