

SPECIFICATION FOR APPROVAL

| | | |
|--------------------------------|-----------|----------------------------|
| CUSTOMER: | | DATE: |
| PART NO: SCM908050-501 | | DWG.NO: SL2270215 |
| CUSTOMER PART NO: | | CUST.DWG.NO: |
| <p>(1) DIMENSION(UNIT: mm)</p> | | A 9.5 ± 0.3 m/m |
| | | B 8.3 ± 0.3 m/m |
| | | C 5.3 (MAX) m/m |
| | | D 1.2 (REF) m/m |
| | | E 7.5 (REF) m/m |
| | | F 6.3 (REF) m/m |
| | | G 2.7 (REF) m/m |
| | | H 4.9 (REF) m/m |
| | | I 10.3 (REF) m/m |
| | | J 6.3 (REF) m/m |
| | | (2)ELECTRICAL REQUIREMENTS |
| Z (Ω) | 500 ± 25% | |
| RDC (mΩ) | 6.5 (MAX) | |
| IDC (A) | 5.0 (MAX) | |
| TEST CONDITION | 100MHz | |
| (4)MATERIAL LIST | | |
| NO/ITEM | | |
| | | |
| | | |
| | | APPROVED BY 吳載敏 |
| | | CHECKED BY 張明德 |
| | | DRAWN BY Vicky |

CORE MASTER ENTERPRISE CO., LTD.

TEL:886-2-8919-1288 FAX:886-2-8919-1298 WEB:www.coremaster.com.tw

TEST DATA

| CUSTOMER: | | | | DATE: | | | | | |
|--|--------------|--------------|--------------|-----------------------|--------------|--------------------|--------------|--------------|--------------|
| PART NO: SCM908050-501 | | | | DWG.NO: SL2270215 | | | | | |
| CUSTOMER PART NO : | | | | CUST.DWG.NO : | | | | | |
| TEST CONDITION: 100MHz | | | | DIMENSION (UNIT : mm) | | | | | |
| ITEM | Z (Ω) | RDC (mΩ) | IDC (A) | A | B | C | D | E | F |
| SPEC | 500 ± 25% | 6.5 (MAX) | 5.0 (MAX) | 9.5 ± 0.3 | 8.3 ± 0.3 | 5.3 (MAX) | 1.2 (REF) | 7.5 (REF) | 6.3 (REF) |
| 1 | 423 | 6.09 | OK | 9.43 | 8.20 | 4.99 | 1.26 | 7.56 | 6.49 |
| 2 | 447 | 5.88 | OK | 9.43 | 8.19 | 5.05 | 1.28 | 7.53 | 6.47 |
| 3 | 442 | 5.82 | OK | 9.41 | 8.18 | 4.99 | 1.30 | 7.52 | 6.47 |
| 4 | 426 | 5.85 | OK | 9.39 | 8.18 | 5.02 | 1.27 | 7.55 | 6.48 |
| 5 | 413 | 6.00 | OK | 9.40 | 8.20 | 4.98 | 1.31 | 7.50 | 6.48 |
| 6 | 449 | 6.02 | OK | 9.42 | 8.24 | 5.01 | 1.27 | 7.52 | 6.47 |
| 7 | 437 | 5.92 | OK | 9.41 | 8.22 | 4.99 | 1.26 | 7.49 | 6.49 |
| 8 | 441 | 6.03 | OK | 9.43 | 8.21 | 4.99 | 1.30 | 7.54 | 6.49 |
| 9 | 442 | 5.92 | OK | 9.43 | 8.19 | 5.00 | 1.31 | 7.56 | 6.48 |
| 10 | 429 | 6.03 | OK | 9.45 | 8.19 | 5.05 | 1.28 | 7.55 | 6.47 |
| X | 435 | 5.96 | | 9.42 | 8.20 | 5.01 | 1.28 | 7.53 | 6.48 |
| R | 36 | 0.27 | | 0.06 | 0.06 | 0.07 | 0.05 | 0.07 | 0.02 |
| TEST INSTRUMENTS HP4191A GKT-502BC CH2816 WR7210 | | | | | | APPROVED BY 吳載敏 | | | |
| | | | | | | CHECKED BY 張明德 | | | |
| | | | | | | DRAWN BY Vicky | | | |

CORE MASTER ENTERPRISE CO., LTD.

TEL:886-2-8919-1288 FAX:886-2-8919-1298 WEB:www.coremaster.com.tw