

## IT FIT 15/220-240/350 CS R

ICUTRONICS FIT CS R | Compact constant current LED driver – Non dimmable



### Product family features

- Supply voltage: 220...240 V
- Line frequency: 50 Hz | 60 Hz
- Line voltage: 198...264 V

### Product family benefits

- Higher quality of light thanks to < 3% output ripple current
- Operating temperature: up to 60 °C
- Flexible current selection via DIP switch
- Reversible overtemperature, overload, short-circuit and open-circuit protection
- High efficiency (up to 92%)

## Areas of application


- Extra small design for integration in small spotlights
- Suitable for luminaires of protection classes I and II
- Suitable for indoor SELV installations

## Technical data


### Electrical data

Nominal input voltage	220...240 V
Mains frequency	50/60 Hz
Input voltage AC	198...264 V
Nominal input current at 230 V	0.08 A
Total harmonic distortion	< 15 %
Power factor $\lambda$	0.75C...0.92C
Efficiency in full-load	90 %
Device power loss	1.6 W
Inrush current	6.8 A
Max. ECG no. on circuit breaker 10 A (B)	63
Max. ECG no. on circuit breaker 16 A (B)	101
Surge capability (L-N)	1 kV
Surge capability (L/N-Ground)	2 kV
Protective conductor current	not relevant
Nominal output voltage	30...40 V
U-OUT (working voltage)	60 V
Nominal output current	250/350 mA
Default output current	350 mA
Output current tolerance	$\pm 5$ %
Output ripple current (100 Hz)	$\leq 3$ %
Output PSTLM	$\leq 1$
Output SVM	$\leq 0.4$
Nominal output power	7.5... 14 W
Maximum output power	14 W
Galvanic isolation primary/secondary	SELV

## Typical Power Factor v Load




## Operating Window




IT FIT 15 CS R Typical Power Factor vs. Load

IT FIT 15 CS R Operating Window

## Typical THD v Load




## Typical Efficiency v Load 230 V 50 Hz



IT FIT 15 CS R Typical THD Vs Load

IT FIT 15 CS R Typical Efficiency vs. Load

## Dimensions & weight



<b>Product weight</b>	40.00 g
<b>Length</b>	48.5 mm
<b>Width</b>	48.5 mm
<b>Height</b>	24.0 mm
<b>Cable cross-section, input side</b>	0.5...1.5 mm <sup>2</sup>
<b>Cable cross-section, output side</b>	0.5...1.5 mm <sup>2</sup>
<b>Wire preparation length, input side</b>	7...8 mm
<b>Wire preparation length, output side</b>	7...8 mm
<b>Cable/wire length, output side</b>	2000 mm

## Colors & materials

<b>Casing material</b>	Plastic
<b>Product color</b>	White

## Temperatures & operating conditions

<b>Ambient temperature range</b>	-20...+60 °C
<b>Maximum temperature at tc test point</b>	75 °C
<b>Max.housing temperature in case of fault</b>	110 °C
<b>Temperature range at storage</b>	-40...+85 °C
<b>Permitted rel. humidity during operation</b>	5...95 %

## Lifespan

ECG lifetime	50000 / 100000 h
--------------	------------------

## Additional product data

Encapsulated	No
--------------	----

## Capabilities

Programming interface	Dipswitch
Dimmable	No
Constant lumen function	No
Max. cable length to lamp/LED module	2.0 m
Suitable for fixtures with prot. class	I / II
Suitable for emergency lighting	No
Type of connection, input side	Push terminal
Type of connection, output side	Push terminal
Suitable for through-wiring	No
Number of channels	1
Overheating protection	Automatic reversible
Overload protection	Automatic reversible
Short-circuit protection	Automatic reversible
Intended for no-load operation	No
No-load proof	Yes

## Programming

Programming device	DIPswitch
Tuner4TRONIC	No
Tuner4TRONIC Field App	No
Box programming	No

## Certificates & standards

Approval marks – approval	CE / ENEC / CCC / RCM
Standards	IEC 61347-1 / IEC 61347-2-13 / IEC 62384 / CISPR 15 / IEC 61000-3-2 / IEC 61000-3-3 / IEC 61547
Type of protection	IP20

## Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	31-03-2026
Primary Article Identifier	6937186134066
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	003ecf00-c40d-46ba-afde-31f330720ab4
SCIP_ID	

## Ecodesign regulation information:

Intended for use with LED modules.

The forward voltage of the LED light source shall be within the defined operating window of the control gear in all operating conditions including dimming if applicable.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

## Download Data

File		
CAD data 3-dim	Compressed	▶ IT FIT 15 CS R CAD3PDF 261125
CAD data	Compressed	▶ IT FIT 15 CS R IGS 261125
CAD data	Compressed	▶ IT FIT 15 CS R STEP 261125
User instruction	PDF	▶ UI IT FIT CS R

## Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
6937186134066 INVENTRONICS	IT FIT 15/220-240/350 CS R	Shipping carton box 20 Pieces	115 x 115 x 150 mm	1.98 dm <sup>3</sup>	43.90 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit