


未注公差/General tolerances(mm)													0.1/10
0 ~ 3	>3 ~ 6	>6 ~ 10	>10 ~ 18	>18 ~ 30	>30 ~ 50	>50 ~ 80	>80 ~ 120	>120 ~ 180	>180 ~ 250	>250 ~ 315	>315 ~ 400	>400 ~ 500	>500
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50

58.0

8.2



IEC60947-7-1

1000V 41A
6mm²

UL1059

600V 50A
20~8AWG **DEGSN**
DS6

UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	600/50	600/50	600/5
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	1000/41	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	8	/	/
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)	0.5~6,10(Sol)/20~8		
间距/Pitch(mm)	8.2		
剥线长度/Stripping length(mm)	10~12		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

4	Current Carrier	Copper	Sn plated
3	Spring	Stainless steel	
2	Button	PA66-GF	UL94 V-0
1	Housing	PA66	UL94 V-0

ITEM	NAME OF PART	MATERIAL	NOTES
------	--------------	----------	-------

REV	ECN	DESCRIPTION	DRFT	DATE
-----	-----	-------------	------	------

MATERIAL: /		SURFACE: /				
MAT NO.: /		 宁波高松电子有限公司 NINGBO DEGSN ELECTRICAL CO., LTD				
STATUS: /						
APPD: Li GL 2020.06.01		NAME: DS6-01P-1Y-00A(H)				
CHKD: Mao J 2020.06.01						
DRFT: Chen K 2020.06.01						
DRAWING NO.: DS6-C01		REV	T0			
	SIZE: A4		TYPE: CUSTOMER DRAWING	SCALE: 2:1	SHEET	1/1