

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless written authorization is granted. Customers will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 非经明确授权, 否则禁止转让、复制、利用、交流本文件的内容, 侵犯者将承担赔偿责任。本公司保留对涉及发明、实用新型和外观设计的所有权利。

FOR-1755 Rev.1.4

2






3

4


5

6

PCB LAYOUT



Please refer to the 3D model, for those unmarked dimensions



4	Spring	Stainless steel	/
3	Button	PA66+GF	UL94V-0
2	Housing	PA10T	UL94V-0
1	Pin header	Copper alloy	Sn plated
ITEM	NAME OF PART	MATERIAL	NOTES

UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	300/12	/	300/10
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	200/17.5	200/17.5	320/17.5
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	2.5	2.5	2.5
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm ²)	28~14/ 0.2~1.5		
间距/Pitch(mm)/线数范围/Poles	3.5/N=02~20P		
剥线长度/Stripping length(mm)	8~9		
使用温度范围/Operating temperature(°C)	-40~+130		
符合 RoHS 环保要求/Conform to: RoHS	Yes		



MATERIAL:	SURFACE/COLOR:
MAT. NO./REV:	MAT STATUS: 批量

APPD: 兰春华	2023.07.13
CHKD: 张玉华	2023.07.13
DRFT: 陈迪辉	2023.07.13

NAME	DG212R-THR-3. 5-XXP-1Y-1000A&Z (H)		
DRAWING NO.	TYPE	DRAWING STATUS	SCALE

200049758	CUSTOMER DRAWING	已发布	2:1
			SHEET 1/1

01		1x Add VDE certification mark	陈迪辉	2023.07.13
REV	ECN	DESCRIPTION	DRFT	DATE

1

2

3

4

5

6