


302270120020

Subminiature DIL relay 2 A



This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

Technical description:

Subminiature DIL relays, PCB mount, 2 pole, CO (nPDT), 2 A, AgNi + Au, DC sensitive coil, 12 V, operating from 8.4 to 18 V, rated power 0.2 W, resistance 720 Ω, consumption 16 mA, holding voltage 4.2 V, must drop-out voltage 0.6 V, version: Wash tight (RT III), ambient temperature from -40 to +85 °C

[BROWSE PRODUCT PAGE](#)

Technical Features:

Ambient temperature range:	-40...85 °C
Commercial Description:	Subminiature dual-in-line relay for PCB mounting with gold plated contacts for assured switching of low level signals, and low coil consumption.
Contact configuration:	2 pole, CO (nPDT)
Dimensions:	10.1x11.4x20.3 mm
Electrical life:	100000 cycles
Insulation coil/contacts:	1.5 kV
Nominal voltage DC:	12 V
Operating range DC:	8.4...18 V
Rated contact voltage:	125 V AC
Rated current (contacts):	2
Rated power DC:	0.2 W
Supply:	DC sensitive coil
Certifications and quality approvals (according to type):	  

The information, technical details, data and features contained in this document are subject to change or modification at any time.
It is for information purposes only and does not form the basis of a contract.

Need more information?
[Contact our sales](#) [Find a dealer](#)