

HSK-Mini


Metr., PG




Material	Nickel plated brass / INOX 1.4305
Seal	Buna-N / TPE / FKM
O-Ring	Buna-N / FKM
Protection	IP 68
Operating Temperature	-20 °C – 100 °C (-4 °F – 212 °F) (Buna-N / TPE) -25 °C – 200 °C (-13 °F – 392 °F) (FKM)



HSK-Mini



HSK-Mini EMC



AG	∅ mm	GL mm	H mm	mm		Number Buna-N / TPE	Number FKM
M 6 x 1	2-3,2	6	10	8		1.106.0601.50	1.106.0600.55
M 8 x 0,75	2-4,5	3,5	14,3	11		1.112.0801.01	
M 8 x 1,25	3-5	6	13	11		1.106.0801.50	1.106.0800.55
M 10 x 1,5	4-6	6	14	12		1.106.1001.50	1.106.1000.55
PG 7	2-4,5	3,5	14,3	11 / 15		1.112.0708.01	
HSK-Mini elongated							
M 8 x 1,25	3-5	10	13	11		1.106.0801.30	1.106.0800.35
M 10 x 1,5	4-6	10	14	12		1.106.1001.30	1.106.1000.35
HSK-Mini EMC							
M 8 x 1,25	3-5	6	13	11		1.119.0800.50	
M 10 x 1,5	4-6	6	14	12		1.119.1000.50	
HSK-Mini INOX							
M 8 x 1,25	3-5	6	13	11		1.129.0800.50	1.129.0800.55
M 10 x 1,5	4-6	6	14	12		1.129.1000.50	1.129.1000.55