

# Specifications



Photo is representative



## Eaton BK/S501-2-R

Eaton S501 Series Fast-acting fuse 2A, 250 Vac or less, 32 Vdc (self certified), BK-S501-2-R

### General specifications

<b>PRODUCT NAME</b>	Eaton Bussmann series S501 fast-acting fuse
<b>CATALOG NUMBER</b>	BK/S501-2-R
<b>UPC</b>	051712648141
<b>PRODUCT HEIGHT</b>	20 mm
<b>PRODUCT WEIGHT</b>	1.06 g
<b>COMPLIANCES</b>	CE Marked RoHS Compliant CCC Marked
<b>CERTIFICATIONS</b>	VDE



Powering Business Worldwide

## Product specifications

<b>AMPERAGE RATING</b>	2 A
<b>FREQUENCY RATING - MAX</b>	50 Hz
<b>FREQUENCY RATING - MIN</b>	50 Hz
<b>VOLTAGE DROP</b>	205 mV typical
<b>INTERRUPT RATING</b>	1.5 kAIC at 250 Vac
<b>FUSE INDICATOR</b>	Non-indicating
<b>CONNECTION</b>	Ferrule end x ferrule end
<b>MATERIAL</b>	Ceramic tube Nickel-plated endcap construction
<b>QUANTITY</b>	100
<b>VOLTAGE RATING</b>	250 Vac or less, 32 Vdc (self certified)
<b>TYPE</b>	Electronic
<b>APPLICATION</b>	Electronic circuits

## Resources

SPECIFICATIONS AND DATASHEETS	<a href="#">Eaton S501 ceramic tube fuses data sheet</a>
-------------------------------	--

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

