seeed studio

INDUSTRIAL PRODUCT DATASHEET

2.13" Quadruple Color eInk / ePaper Display with 122x250 Pixels, additional yellow and red display, SPI interface, Support XIAO/Arduino

A 2.13" Quadruple Color eInk Display with SPI interface, delivering clear, low-power visuals for smart wearables and electronic shelf labels.

SKU	UPDATED	PRICE
104990846	2026-06-01 02:43:59	$7.50(Excl. VAT)



Overview



The 2.13" Quadruple Color eInk Display offers exceptional readability, ultra-low power consumption, and eye-friendly viewing. It is natively compatible with XIAO ePaper Driver Boards and supports seamless setup via SenseCraft HMI for applications like reading equipment, mobile devices, and electronic tags.

Key Features

- **Plug & Play with XIAO ePaper Driver Boards:** Natively compatible with a range of 24-pin ePaper displays via the **ePaper Display Board**, these ready-to-use controller boards offer features such as an optional battery connector and a user button to accelerate prototyping and project development.
- **Exceptional Readability:** The display's reflective properties ensure effortless legibility of text and images in different lighting environments.
- **Ultra-Low Power Consumption:** The ePaper consumes power only during updates, resulting in longer battery life and greater energy efficiency.
- **Eye-Friendly and Heat-free:** Eliminate glare, providing a comfortable viewing experience while remaining cool without generating heat.

Seamless Setup and Customization for Your ePaper Display

This ePaper display is designed to work seamlessly with any standard 40-pin driver board. We recommend the **XIAO ePaper Display Board EE04** or **XIAO ePaper Display Board EE05**.

To make things even easier, we're introducing **SenseCraft HMI**—a no-code, AI-powered platform that allows you to quickly design and customize your user interface. Drag and drop elements, choose templates, or let AI generate the perfect layout for you.Get started today and create your ideal display experience with ease!

Product Gallery











Specification

Parameters	Details
Driver IC	SSD1680
Type	Dot Matrix

Size	2.13 inch
Active Area(mm)	48.55 x 23.7046
Resolution	122 x 250 pixels
Pixel Pitch(mm)	0.1943 x 0.1942
Display Color	Black, White, Yellow and Red
Interface	SPI
Connector	24 Pin FPC, 0.5mm Pitch
Viewing Angle	>170°
Operating Voltage	3.3V
Operating Temperature	0-40°C
Driver Mode	Support XIAO/Arduino/MicroPython
Drawing	Support GUI Drawing
Power Consumption	9.9mW (typ.)
Standby Consumption	0.003mW
Outline Dimension(mm)	59.2 x 29.2 x 1.00
Weight	3.2g

Hardware Overview



Applications

- **Reading equipment**
- **Mobile device**
- **Electronic tags and price tags**
- **Smart Wearables**
- **Electronic Shelf Labels**
- **Smart Card**

Product						
Processor	XIAOESP32-S3 Plus	XIAOnRF52840 Plus	XIAOESP32-S3 Plus	XIAOnRF52840 Plus	N/A(Compatible with XIAO Series)	
Compatible Displays	24 Pin ePaper	24 Pin ePaper50 Pin ePaper	24 Pin ePaper			
Battery Connector	JST 2.0mm	JST 2.0mm	JST 2.0mm	/		
Battery Power ON/OFF	√	√	√	/		
Button	1x Reset,3x User	1x Reset,3x User	/			
Extension IO Port	√	/	√			
SenseCraft HMI	√	/	√	/	/	

Product	**Name**	**Resolution**	**Display Color**	**Partial Refresh**	**SenseCraft HMI**
		200x200		√	√
		250x122		√	√
		250×122			√
		212x104		√	
		296x128			
		296x128		√	√
		296x128			√
		400x300		√	
		800x480			√
		648x480		√	
		800x480		√	
		800x480		√	√
		1404×1872		√	√
		1600x1200			√

Compliance & Logistics

2.13" Quadruple Color ePaper Display	×1

Resource Links

- https://www.seeedstudio.com/2-13-Quadruple-Color-ePaper-Display-with-122x250-Pixels-p-5779.html
- 2.13-inch Quadruple ePaper Display Datasheet

Seeed Technology Co.,Ltd.
9F, Building G3, International E City,
Zhongshanyuan Road, Nanshan, Shenzhen, China

Tel: +86 0755-80695676
Web: www.seeed.cc
Shop: www.seeedstudio.com