

YASMEEN-25-FR-S

~9° ultra-narrow spot beam

SPECIFICATION:

Dimensions	Ø 24.8
Height	15.9 mm
Fastening	socket
ROHS compliant	yes ⓘ

MATERIALS:

Component	Type	Material	Colour	Finish	Length (mm)
YASMEEN-25-FR-S	Single lens	PMMA	clear		



ORDERING INFORMATION:


Component	Qty in box	MOQ	MPQ	Box weight (kg)
L20339_YASMEEN-25-FR-S » Box size: 476 x 273 x 197 mm	3380		130	5.1
LP20341_YASMEEN-25-FR-S-B-WHT » Box size: 480 x 280 x 300 mm	1690	130	130	5.1
LP20340_YASMEEN-25-FR-S-B » Box size: 480 x 280 x 300 mm	1690	130	130	4.7



OPTICAL RESULTS (SIMULATED):




LED V3 HD Gen 8
Ordering code LP20340_YASMEEN-25-FR-S-B
FWHM / FWTM 12.0° / 20.0°
Efficiency 39 %
Peak intensity 7.7 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files




LED V3 HD Gen 8
Ordering code LP20341_YASMEEN-25-FR-S-B-WHT
FWHM / FWTM 12.0° / 20.0°
Efficiency 62 %
Peak intensity 7.8 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files



LED V4 HD Gen 8
Ordering code LP20340_YASMEEN-25-FR-S-B
FWHM / FWTM 14.0° / 22.0°
Efficiency 39 %
Peak intensity 5.6 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:




Light distribution files

OPTICAL RESULTS (SIMULATED):




LED V4 HD Gen 8
 Ordering code LP20341_YASMEEN-25-FR-S-B-WHT
 FWHM / FWTM 14.0° / 23.0°
 Efficiency 62 %
 Peak intensity 5.6 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files




LED V6 HD Gen 8
 Ordering code LP20341_YASMEEN-25-FR-S-B-WHT
 FWHM / FWTM 21.0° / 33.0°
 Efficiency 78 %
 Peak intensity 3.3 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 L20109_SOCKET-B-25-C



Light distribution files



LED V6 HD Gen 8
 Ordering code LP20340_YASMEEN-25-FR-S-B
 FWHM / FWTM 21.0° / 32.0°
 Efficiency 39 %
 Peak intensity 2.7 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 L20109_SOCKET-B-25-C




Light distribution files

OPTICAL RESULTS (SIMULATED):

CITIZEN


LED	CLU700/701/702/703
Ordering code	LP20340_YASMEEN-25-FR-S-B
FWHM / FWTM	20.0° / 30.0°
Efficiency	37 %
Peak intensity	2.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

CITIZEN


LED	CLU700/701/702/703
Ordering code	LP20341_YASMEEN-25-FR-S-B-WHT
FWHM / FWTM	20.0° / 31.0°
Efficiency	58 %
Peak intensity	2.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

CITIZEN

LED	CLU7A2/7A3
Ordering code	LP20340_YASMEEN-25-FR-S-B
FWHM / FWTM	14.0° / 23.0°
Efficiency	38 %
Peak intensity	5.3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	




Light distribution files

OPTICAL RESULTS (SIMULATED):

CITIZEN


LED	CLU7A2/7A3
Ordering code	LP20341_YASMEEN-25-FR-S-B-WHT
FWHM / FWTM	14.0° / 24.0°
Efficiency	61 %
Peak intensity	5.4 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

CITIZEN


LED	CLU7L3
Ordering code	LP20340_YASMEEN-25-FR-S-B
FWHM / FWTM	9.0° / 16.0°
Efficiency	38 %
Peak intensity	12.1 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

CITIZEN

LED	CLU7L3
Ordering code	LP20341_YASMEEN-25-FR-S-B-WHT
FWHM / FWTM	9.0° / 16.0°
Efficiency	60 %
Peak intensity	12.2 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	




Light distribution files

OPTICAL RESULTS (SIMULATED):

CITIZEN


LED	CLU7S3
Ordering code	LP20340_YASMEEN-25-FR-S-B
FWHM / FWTM	12.0° / 20.0°
Efficiency	38 %
Peak intensity	7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

CITIZEN


LED	CLU7S3
Ordering code	LP20341_YASMEEN-25-FR-S-B-WHT
FWHM / FWTM	12.0° / 20.0°
Efficiency	60 %
Peak intensity	7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files



LED	NV4WB35AM
Ordering code	LA20342_YASMEEN-25-FR-S
FWHM / FWTM	12.0° / 20.0°
Efficiency	34 %
Peak intensity	7.1 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 7
FI-24100 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Poznan, Poland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)