


Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非经予明确授权，否则禁止将此文件的内容复制或传播给他人，及将其用于其他用途。违反者将为赔偿责任。本公司保留对涉及专利、实用新型和外观专利的所有权利。


未注公差/General tolerances(mm)

0~3	>3~6	>6~10	>10~18	>18~30	>30~50	>50~80	>80~120	>120~180	>180~250	>250~315	>315~400	>400~500	>500	0.1/10
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2°









PCB LAYOUT

Note:The A&Z(H) in the name means:A(H) and Z(H).

ITEM	NAME OF PART	MATERIAL	NOTES
3	Screw	Steel	Ni Plated
2	Pin header	Copper alloy	Sn Plated
1	Housing	PA66	UL94V-0

	B	C	D
UL 标准/UL Standard:	300/20	/	/
额定电压/电流/Rated Voltage(V)/Current(A)	M3, 0.5/4.43		
螺丝扭矩/Torque Tightening(N·m/Lb.in)	22~12		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG)	8.25/N=02~22P		
间距/Pitch(mm)/线数范围/Poles	-40~+105		
使用温度范围/Operating temperature(°C)	Yes		
符合RoHS环保要求/Conform to RoHS			

REV	ECN	DESCRIPTION	DRFT	DATE
00				

DEGSON

APPD:	蓝贵凡	2023.06.06
CHKD:	曹利彬	2023.06.06
DRFT:	娄民洁	2023.06.06

A4 mm (inch)

MATERIAL: | SURFACE/COLOR:

MAT NO./REV: - / 00 | MAT STATUS: 批量

NAME: DG36S-B-XXP-1Y-00A&Z(H)

DRAWING NO.	TYPE	DRAWING STATUS	SCALE	SHEET
200066717	CUSTOMER DRAWING	已发布	2:1	1/1