

SPECIAL TOOLS

No.	Description	Length	Weight	
1-909	Engineer's mirror , magnifying, concave mirror 23 mm Ø, with extension handle, made entirely from BERNSTEINIT, fully insulated version	145/260 mm	9 g	
1-978	Engineer's mirror as above, but extension handle with ground 6 mm screwdriver blade, made from BERNSTEINIT	145/260 mm	9 g	
2-275	Repair mirror , stainless, magnifying, concave mirror 21 mm Ø, with BERNSTEINIT handle	180 mm	7 g	
2-281	Double-jointed mirror , slewable into any position, nickel-plated, with insulated handle and clip, mirror 30 mm Ø	195 mm	33 g	
2-282	Telescopic mirror with double joint, slewable into any position, nickel-plated, pocket clip, mirror 23 mm Ø	150-460 mm	21 g	
2-285	Inspection mirror with illuminated mirror area and double joint, slewable into any position, nickel-plated, pocket clip, for 2 batteries type Mignon 1.5 V	200 mm	43 g	
2-291	Plastic magnifying glass with biconvex lens, 5 x magnification, 30 mm Ø, short, practical shape	70 mm	6 g	
2-293	Hand magnifier , biconvex PMX-light-weight lens with antistatic coating, 65 mm Ø, 3.0 x magnification	180 mm	52 g	
2-295	Hand magnifier, illuminated with aspherical PMX-light-weight lens, 35 mm Ø, 7x magnification, 28.0 Dpt., with 2 batteries type Mignon 1.5 V	125 mm	80 g	
2-297	Magnifying glasses Max Detail for easy and precise viewing, 2 x magnification (galilean system), large field of view: about Ø 15 cm, with 40 cm distance, large working distance: 40 cm, magnifying glasses with +/- 3 diopter adjustment, independently adjustable		52 g	
2-655	Pocket inspection lamp MITILITE LASER SPOT with bent fibre optic adaptor for close inspection of small, tight, hard-to-see areas. The most powerful pocket lite with pre-focused reflector, clip and magnet, handy, watertight and unbreakable incl. 2 Alkaline-batteries ea. 1.5 V	125 mm	52 g	
2-655-80	Pocket inspection lamp as discribed above, with additional straight fibre optic adapter, 80 mm long			

SPECIAL TOOLS

No.	Description	Length	Weight
-----	-------------	--------	--------



2-130	Set of spring hooks , 6-piece, nickel-plated, for gripping and straightening, inserting and removing tension and compression springs of various kinds, hook screwing onto handle, in a plastic case	hook with handle 205 mm	42 g
-------	--	----------------------------	------



2-131	Spring hook , nickel-plated and insulated, for inserting and removing tension and compression springs	205 mm	10 g
-------	--	--------	------



2-132	Spring hook , nickel-plated and insulated, for inserting and removing tension springs	175 mm	8 g
-------	--	--------	-----



2-133	Spring hook with ring , nickel-plated, for inserting and removing strong tension springs	195 mm	13 g
-------	---	--------	------



2-306	Extractor with self-centring extractor hook to remove small bearings and similar parts. Span 60 mm, grip depth 50 mm	105 mm	205 g
-------	---	--------	-------



2-601	IC tweezers for gripping, inserting and removing, especially suitable for narrow components, nickel-plated	125 mm	20 g
-------	---	--------	------



2-601-13	IC-tweezers with ESD-coating description as before	125 mm	22 g
----------	--	--------	------



2-605	PLCC-puller for lifting out plug-in PLCC's	135 mm	6 g
-------	---	--------	-----



2-620	PLCC extractor for easy removal of plug-in PLCC's	100 mm	22 g
-------	--	--------	------