


# STL950/..-5.0-V-GREEN



### Technical Data

Wire Sizes	Insulating Material
Solid min -	Material PA 6.6
Solid max -	Flammability Class UL 94 V-0
Stranded (flexible) -	<b>Temperatures</b>
min -	Operating Temperature -30 °C - 105 °C
Stranded (flexible) -	<b>Wave Soldering Process</b>
max -	Soldering Temperature, recommended 265 °C
Stranded with Ferrule -	Peak Soldering Time, recommended 3-4 s
min -	<b>Reflow Process</b>
Stranded with Ferrule -	Soldering Temperature, recommended -
max -	Peak Soldering Time, recommended -
<b>Dimensions</b>	
Stripped Length	
PCB Hole Diameter 1.4 mm	
<b>Materials</b>	
Contact Pin Copper Alloy	

### Colours


	GREEN, RAL6018
	BLACK, RAL9011
	BASALT GREY, RAL7012
	LIGHT GREY, RAL7035
	LIGHT GREEN, similar RAL 6018

Colours according to RAL, there may be variations on colour due to production conditions. Special colours on request.

### Counterparts (Spacing 5.0 mm)

Pin Strip/Terminal Blocks				
AK950	AK4951	AK3950	AK1110	AK1100

If there are combinations with different ratings, the lower value is valid.



### Order Data (Spacing 5.0 mm)

Poles	Width (mm)	Article Designation	Article Number	PU
2	10.00	STL950/2-5.0-V-GREEN	50950025111F	200
3	15.00	STL950/3-5.0-V-GREEN	50950035111F	200
4	20.00	STL950/4-5.0-V-GREEN	50950045111F	200
5	25.00	STL950/5-5.0-V-GREEN	50950055111E	100
6	30.00	STL950/6-5.0-V-GREEN	50950065111E	100
7	35.00	STL950/7-5.0-V-GREEN	50950075111E	100
8	40.00	STL950/8-5.0-V-GREEN	50950085111D	50
9	45.00	STL950/9-5.0-V-GREEN	50950095111D	50
10	50.00	STL950/10-5.0-V-GREEN	50950105111D	50
11	55.00	STL950/11-5.0-V-GREEN	50950115111D	50
12	60.00	STL950/12-5.0-V-GREEN	50950125111D	50
13	65.00	STL950/13-5.0-V-GREEN	50950135111D	50
14	70.00	STL950/14-5.0-V-GREEN	50950145111D	50
15	75.00	STL950/15-5.0-V-GREEN	50950155111D	50
16	80.00	STL950/16-5.0-V-GREEN	50950165111D	50
17	85.00	STL950/17-5.0-V-GREEN	50950175111D	50
18	90.00	STL950/18-5.0-V-GREEN	50950185111D	50
19	95.00	STL950/19-5.0-V-GREEN	50950195111D	50
20	100.00	STL950/20-5.0-V-GREEN	50950205111D	50
21	105.00	STL950/21-5.0-V-GREEN	50950215111D	50
22	110.00	STL950/22-5.0-V-GREEN	50950225111D	50
23	115.00	STL950/23-5.0-V-GREEN	50950235111D	50
24	120.00	STL950/24-5.0-V-GREEN	50950245111D	50

### Accessories

Figure	Designation	Article Number
	Coding star CS2-5.0/5.08-RED	50000000024
	Dividing element SE-STL950-GREEN	50950000002

### Ratings



Usegroup	B	C	D	
Rated Voltage	300 V	150 V	300 V	250 V
Rated Current	15 A	15 A	10 A	12 A
Overvoltage Category				III
Test Voltage	1.6 kV	1.6 kV	1.6 kV	4.0 kV
Pollution Degree				3