



**VOLTAGE RANGE: 50 --- 600 V**

**CURRENT: 1.0 A**


### Features

- ✧ Low cost
- ✧ Low leakage
- ✧ Low forward voltage drop
- ✧ High current capability
- ✧ Easily cleaned with Alcohol, Isopropanol and similar solvents
- ✧ The plastic material carries U/L recognition 94V-0

### Mechanical Data

- ✧ Case: JEDEC DO-214AC, molded plastic
- ✧ Terminals: Solderable per MIL-STD-202, Method 208
- ✧ Polarity: Color band denotes cathode
- ✧ Weight: 0.002 ounces, 0.064 grams
- ✧ Mounting position: Any

### DO-214AC(SMA)



Dimensions in millimeters

### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate by 20%.

|   |                 | ES1A            | ES1B | ES1C | ES1D | ES1G | ES1H | ES1J | UNITS              |
|---|-----------------|-----------------|------|------|------|------|------|------|--------------------|
| Maximum recurrent peak reverse voltage  | $V_{RRM}$       | 50              | 100  | 150  | 200  | 400  | 500  | 600  | V                  |
| Maximum RMS voltage   | $V_{RMS}$       | 35              | 70   | 105  | 140  | 280  | 350  | 420  | V                  |
| Maximum DC blocking voltage   | $V_{DC}$        | 50              | 100  | 150  | 200  | 400  | 500  | 600  | V                  |
| Maximum average forward rectified current<br>@ $T_A=75^\circ\text{C}$   | $I_{F(AV)}$     | 1.0             |      |      |      |      |      |      | A                  |
| Peak forward surge current<br>8.3ms single half-sine-wave<br>superimposed on rated load @ $T_J=125^\circ\text{C}$ | $I_{FSM}$       | 30              |      |      |      |      |      |      | A                  |
| Maximum instantaneous forward voltage at 1.0 A  | $V_F$           | 0.98            |      |      |      | 1.25 | 1.70 |      | V                  |
| Maximum reverse current @ $T_A=25^\circ\text{C}$<br>at rated DC blocking voltage @ $T_A=125^\circ\text{C}$        | $I_R$           | 5.0<br>200      |      |      |      |      |      |      | $\mu\text{A}$      |
| Typical reverse recovery time (Note1)   | $t_{rr}$        | 35              |      |      |      |      |      |      | ns                 |
| Typical junction capacitance (Note2)  | $C_J$           | 19              |      |      |      |      |      |      | pF                 |
| Typical thermal resistance (Note3)  | $R_{\theta JA}$ | 50              |      |      |      |      |      |      | $^\circ\text{C/W}$ |
| Operating junction temperature range  | $T_J$           | - 55 ---- + 150 |      |      |      |      |      |      | $^\circ\text{C}$   |
| Storage temperature range   | $T_{STG}$       | - 55 ---- + 150 |      |      |      |      |      |      | $^\circ\text{C}$   |


NOTE: 1. Measured with  $I_F=0.5\text{A}$ ,  $I_R=1\text{A}$ ,  $I_{rr}=0.25\text{A}$ .

2. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.

3. Thermal resistance from junction to ambient and junction to lead P.C.B. mounted on 0.27"X0.27"(7.0X7.0mm<sup>2</sup>) copper pad areas

## Ratings And Characteristic Curves


**FIG.1 -- TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTIC**




NOTES: 1. RISE TIME = 7ns MAX. INPUT IMPEDANCE = 1MΩ. 22pF.  
 2. RISE TIME = 10ns MAX. SOURCE IMPEDANCE = 50 Ω.

SET TIME BASE FOR 10/15 ns/cm


**FIG.2 -- TYPICAL FORWARD CHARACTERISTIC**



**FIG.3 -- FORWARD DERATING CURVE**



**FIG.4 -- TYPICAL JUNCTION CAPACITANCE**



**FIG.5 -- PEAK FORWARD SURGE CURRENT**

