

**Kingbright®****SURFACE MOUNT LED LAMPS**

KM-23



Part No.	Emitting Colour + Material	Wave-length (nm)	Lens Type	Iv (mcd) @20mA		Viewing Angle	Dimension
				Min.	Typ.		
KM-23HD	GaP	700	red diffused	0,5	1,25	140°	<b>SOT -23 Surface Mount LED Lamp (3.0 mm x 1.3 mm)</b> 
KM-23HT	GaP	700	red transparent	0,5	1,25	140°	
KM-23HC	GaP	700	water clear	0,5	1,25	140°	
KM-23ID	GaAsP/GaP	625	red diffused	8	32	140°	
KM-23IT	GaAsP/GaP	625	red transparent	8	32	140°	
KM-23EC	GaAsP/GaP	625	water clear	8	32	140°	
KM-23SGD	GaP	565	green diffused	8	32	140°	
KM-23SGT	GaP	565	green transparent	8	32	140°	
KM-23SGC	GaP	565	water clear	8	32	140°	
KM-23YD	GaAsP/GaP	590	yellow diffused	5	12,5	140°	
KM-23YT	GaAsP/GaP	590	yellow transparent	5	12,5	140°	
KM-23YC	GaAsP/GaP	590	water clear	5	12,5	140°	
KM-23SRD	GaAlAs	660	red diffused	50	90	140°	
KM-23SRT	GaAlAs	660	red transparent	50	90	140°	
KM-23SRC	GaAlAs	660	water clear	50	90	140°	
KM-23SYD	InGaAlP	595	yellow diffused	40	100	140°	
KM-23SYT	InGaAlP	595	yellow transparent	40	100	140°	
KM-23SYC	InGaAlP	595	water clear	40	100	140°	
KM-23ESGW	GaAsP/GaP	625	white diffused	8	32	140°	
	GaP	565					
KM-23ESGC	GaAsP/GaP	625	water clear	8	32	140°	
	GaP	565					

