


R13-112



Ø 20.2

2.5 mm max for X8

3 mm max

20A 12V DC

10A 28V DC

6A 12VT

* Waterproof boot (R13-112-12) is optional (refer page 69).



10A 28V DC, 6A 12VT
N/A A8, B8, B8F, C8, D8, E8, F8

ROCKER

A/B/B10 BF/C/D E/F/G H/I	B2 B2F	A8/B8 B8F C8/D8 E8/F8
A2	B9 B9F	AP BP CP DP
A28	L L3 LF CL/DL	
A5	LP	



FUNCTION

A OFF 2P SPST ON	B P OFF 3P SPST (ILLUMINATED) ON	D P ON OFF OFF 3P SPDT
A 2 OFF 2P SPST ON	B F OFF 3P SPST (ILLUMINATED) (ON)	D L ON OFF ON 4P SPDT (LED)
A 2 B OFF 2P SPST ON	B 2 F OFF 3P SPST (ILLUMINATED) (ON)	E OFF ON 2P SPST
A 5 OFF 2P SPST (Gloss Finish) ON	B 8 F OFF 3P SPST (ILLUMINATED) (ON)	E 8 OFF ON 2P SPST
A 8 OFF 2P SPST ON	B 9 F OFF 3P SPST (ILLUMINATED) (ON)	F OFF ON 2P SPST
A P OFF 2P SPST ON	C ON ON 3P SPDT	F 8 OFF ON 2P SPST
B OFF 3P SPST (ILLUMINATED) ON	C 8 ON ON 3P SPDT	G ON ON 3P SPDT
B 2 OFF 3P SPST (ILLUMINATED) ON	C P ON ON 3P SPDT	H ON OFF ON 3P SPDT
B 8 OFF 3P SPST (ILLUMINATED) ON	C L ON ON 4P SPDT (LED)	I ON OFF ON 3P SPDT
B 9 OFF 3P SPST (LED) ON	D ON OFF ON 3P SPDT	L OFF ON 4P SPST (LED)
B 1 0 OFF 3P SPST (LED) ON	D 8 ON OFF ON 3P SPDT	L 3 OFF ON 4P SPST (LED)
		L F OFF ON 4P SPST (LED)
		L P OFF ON 4P SPST (LED)

TERMINAL

0 2 □ .187" SQ

0 9 ▽ PC
A/C/D/E/F/G/H/I

1 2 ○ SO
A/C/D/E/F/G/H/I/L

► For wire connector, please refer to page 66 (R4-57)

