


R13-66



16A 12V DC
6-10A 28V DC

* Waterproof boot (R13-66A-29) is optional (refer page 69).



16A 12V DC, 6A 28V DC



16A 12V DC, 10A 28V DC for A8, B8, B8F, C8, F8



16A 12V DC, 10A 28V DC, 6A 14VT for A, B, C, D, E, F, G, H, I, L

R13-66		
	X	Y
	X	Y
0.75-1.25	19.2±0.1	13.0±0.1
1.25-2	19.4±0.1	13.0±0.1
2-3	19.8±0.1	13.0±0.1

R13-66 8		
	X	Y
	X	Y
0.75-1.5	19.4±0.1	13.0±0.1
1.25-2.5	19.8±0.1	13.0±0.1

FUNCTION

A OFF ON 2P SPST	B 6 OFF ON 3P SPST (LED or LAMP)	F 8 OFF (ON) 2P SPST	
A 5 OFF ON 2P SPST	B 6 F OFF (ON) 3P SPST (LED)	G ON (ON) 3P SPDT	
A 8 OFF ON 2P SPST	B 8 OFF ON 3P SPST (LED)	H ON OFF (ON) 3P SPDT	
A P OFF ON 2P SPST	B 8 F OFF (ON) 3P SPST (LED)	HP ON OFF (ON) 3P SPDT	
B OFF ON 3P SPST (LED or LAMP)	C ON ON 3P SPDT	I (ON) OFF (ON) 3P SPDT	
B F OFF (ON) 3P SPST	C P ON ON 3P SPDT	IP (ON) OFF (ON) 3P SPDT	
B 2 OFF ON 3P SPST (LED or LAMP)	C 8 ON ON 3P SPDT	L OFF ON 4P SPST (LED)	
B 2 F OFF (ON) 3P SPST (LED)	D ON OFF ON 3P SPDT	LP OFF ON 4P SPST (LED)	
B 4 OFF ON 3P SPST (LED)	DP ON OFF ON 3P SPDT	TERMINAL	
B 4 F OFF (ON) 3P SPST (LED)	E (OFF) ON 2P SPST	0 2 .187" SQ	
	F OFF (ON) 2P SPST	0 5 S0 A/C/D/E/F/G/H/I	
		0 9 PC A/C/D/E/F/G/H/I	
		1 0 PC ANGLE A/C/D/E/F/G/H/I	
		1 2 S0 A/C/D/E/F/G/H/I/L	

ROCKER

A/B/BF/C/D/E/F G/H/I B, BF transparent	AP/CP/DP/HP/IP
A5 B, BF transparent	B6/B6F B6, B6F transparent
B2/B2F 	A8/B8/B8F/C8 F8
L/B4/BF4 	

