

Country of Origin : China  
 Operating Temperature : 0~40 [°C]  
 Dimension : 59 x 26 x 41 [mm]

Efficiency level (ErP) :



Approvals / Marks :



**Features:**

Wide range Input (90 ~ 264)VAC / (47 ~ 63) Hz.

RoHS conform.

Over load, over voltage & short protection.

**Specification:**

	Model	Voltage DC [V]	Loading [A]	Tol. [V]	OCP [A]	OVP max [V]	Efficiency [%]	Max. Power [W]	Ripple & Noise [mV]p-p	Connector [mm]
ErP V.	SYS1000-0305-W2E	5	0.0~0.5	4.75~5.25	0.55~1A	8V max.	≥67.97	3	200	2.1x5.5x11
	SYS1000-0309-W2E	9	0.0~0.3	8.55~9.45	0.33~0.6A	15V max.	≥68.46	3	200	2.1x5.5x11
	SYS1000-0312-W2E	12	0.0~0.25	11.4~12.6	0.3~0.5A	18V max.	≥69	3	200	2.1x5.5x11
INPUT	Voltage	(90 ~ 264) VAC								
	Frequency	(47 ~ 63) Hz								
	Current	The input current must be less than 0.4A at 100-240Vac input & Full load.								
	Inrush Current (cold start)	The inrush current must be less than 30A at 240Vac input and full load.								
	Surge Current max.	40Amax. @ power supply cold start, ambient temperature 25°C @ 115Vac/230Vac nominal AC input.								
	Leakage current	0.25mA Max.								
PROTECTION	Over load	OCP	The power supply shall be self-recovering when the fault condition is removed.							
	Over Voltage	OVP	The power supply shall be self-recovering when the fault condition is removed.							
	Short Circuit	The adaptor shall hiccup and the input power shall decrease when the output is shorted, the power supply shall have no damage, and can be self-recovered when the fault condition is removed.								
	Input protection	10R 1W The power supply shall be protected against power line surges and any abnormal condition								
	Protection class	II.								
OTHERS	Insulation Resistance	Input to output: 50M OHM at 500VDC.								
	Dielectric Strength	I/P-O/P (FG): 3KVAC / 10mA / 1 min								
	Turn on delay	3Sec max. @ AC low line input @ output full load								
	Hold-up Time	4ms Min. @ AC nominal Input and Output full load (1 half cycle)								
	MTBF Qualification	50K hours full rated load operation at 25°C, according to the MIL-STD-217F.								
	DC cable & connector	2468#26AWG*2C/4.5feet PVC BLACK 80°C - 2.1*5.5*11mm/180° Center "+" or depends on request								
	Average Efficiency	The efficiency shall be higher than >=67.97% - >=69% typical while measuring at nominal line and maximum load.(Meet Energy level V)								
	Standby Power	The standby power must be less than 0.3W at 100-240Vac input.								
	Start-Up and Turn-off	The start-up time (Ton) : 4seconds Max.   The output rise time (Trise) : 25ms Max.								
ENVIRONMENT	Temperature	Operating: (0 ~ 40)°C / Storage: (-20 ~ 85)°C								
	Humidity	Operating: (10 ~ 90)% RH / Storage: (5 ~ 95)% RH non condensing								
<b>SAFETY</b>		<b>CE   TUV/GS   CB</b>								
EMC	EN55022:2010   EN55024:2010   EN61000-3-2:2006+A1:2009+A2:2009   EN61000-3-3:2008									
	EN60950-1:2006+A11+A1+A12   EN61558-1:2005+A1   EN61558-2-16:2009									
WEIGHT	1pc	N.W.: 55g / pc								
		0.265x 0.325 x 0.465[m]								
PACKING	Box	150 pcs / 1box								
		G.W.: 10.5kg / box								

Mechanical case specification:

