




## P-channel Enhancement-mode Power MOSFET

**Simple Gate Drive**

**Small Package Outline**

**Low Gate Charge**

**RoHS-compliant, halogen-free**




$BV_{DSS}$	-20V
$R_{DS(ON)}$	145mΩ
$I_D$	-1.8A

## Description

Advanced Power MOSFETs from APEC provide the designer with the best combination of fast switching, low on-resistance and cost-effectiveness.

The AP2325GEU6-HF-3 is in the popular SOT-363 ultra-small surface-mount package which is widely used in commercial and industrial applications where a small board footprint is required.

This device is well suited for use in applications such as load switches.



## Absolute Maximum Ratings

Symbol	Parameter	Rating	Units
$V_{DS}$	Drain-Source Voltage	-20	V
$V_{GS}$	Gate-Source Voltage	$\pm 12$	V
$I_D$ at $T_A = 25^\circ\text{C}$	Continuous Drain Current <sup>3</sup>	-1,8	A
$I_D$ at $T_A = 70^\circ\text{C}$	Continuous Drain Current <sup>3</sup>	-1.5	A
$I_{DM}$	Pulsed Drain Current <sup>1</sup>	-7.2	A
$P_D$ at $T_A = 25^\circ\text{C}$	Total Power Dissipation	0.74	W
$T_{STG}$	Storage Temperature Range	-55 to 150	°C
$T_J$	Operating Junction Temperature Range	-55 to 150	°C

## Thermal Data

Symbol	Parameter	Value	Unit
$R_{thj-a}$	Maximum Thermal Resistance, Junction-ambient <sup>3</sup>	170	°C/W

## Ordering Information

**AP2325GEU6-HF-3TR** RoHS-compliant halogen-free SOT-363, shipped on tape and reel, 3000pcs/reel



**Electrical Specifications at  $T_j=25^\circ\text{C}$  (unless otherwise specified)**

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$\text{BV}_{\text{DSS}}$	Drain-Source Breakdown Voltage	$V_{\text{GS}}=0\text{V}$ , $I_{\text{D}}=-250\mu\text{A}$	-20	-	-	V
$R_{\text{DS}(\text{ON})}$	Static Drain-Source On-Resistance <sup>2</sup>	$V_{\text{GS}}=-4.5\text{V}$ , $I_{\text{D}}=-1.5\text{A}$	-	120	145	$\text{m}\Omega$
		$V_{\text{GS}}=-2.5\text{V}$ , $I_{\text{D}}=-1.0\text{A}$	-	145	200	$\text{m}\Omega$
$V_{\text{GS}(\text{th})}$	Gate Threshold Voltage	$V_{\text{DS}}=V_{\text{GS}}$ , $I_{\text{D}}=-250\mu\text{A}$	-0.3	-0.7	-1	V
$g_{\text{fs}}$	Forward Transconductance	$V_{\text{DS}}=-5\text{V}$ , $I_{\text{D}}=-1\text{A}$	-	4.6	-	S
$I_{\text{DSS}}$	Drain-Source Leakage Current	$V_{\text{DS}}=-16\text{V}$ , $V_{\text{GS}}=0\text{V}$	-	-	-10	$\mu\text{A}$
$I_{\text{GSS}}$	Gate-Source Leakage	$V_{\text{GS}}=\pm 12\text{V}$ , $V_{\text{DS}}=0\text{V}$	-	-	$\pm 30$	$\mu\text{A}$
$Q_g$	Total Gate Charge	$I_{\text{D}}=-1\text{A}$ $V_{\text{DS}}=-10\text{V}$ $V_{\text{GS}}=-4.5\text{V}$	-	6	9.6	nC
$Q_{\text{gs}}$	Gate-Source Charge		-	1	-	nC
$Q_{\text{gd}}$	Gate-Drain ("Miller") Charge		-	2	-	nC
$t_{\text{d}(\text{on})}$	Turn-on Delay Time	$V_{\text{DS}}=-10\text{V}$ $I_{\text{D}}=-1\text{A}$ $R_{\text{G}}=3.3\Omega$ $V_{\text{GS}}=-5\text{V}$	-	4	-	ns
$t_r$	Rise Time		-	22	-	ns
$t_{\text{d}(\text{off})}$	Turn-off Delay Time		-	16	-	ns
$t_f$	Fall Time		-	18	-	ns
$C_{\text{iss}}$	Input Capacitance	$V_{\text{GS}}=0\text{V}$ $V_{\text{DS}}=-10\text{V}$ $f=1.0\text{MHz}$	-	500	800	pF
$C_{\text{oss}}$	Output Capacitance		-	70	-	pF
$C_{\text{rss}}$	Reverse Transfer Capacitance		-	55	-	pF

### Source-Drain Diode

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$V_{\text{SD}}$	Forward On Voltage <sup>2</sup>	$I_{\text{S}}=-0.6\text{A}$ , $V_{\text{GS}}=0\text{V}$	-	-	-1.2	V
$t_{\text{rr}}$	Reverse Recovery Time	$I_{\text{S}}=-1\text{A}$ , $V_{\text{GS}}=0\text{V}$ ,	-	15	-	ns
$Q_{\text{rr}}$	Reverse Recovery Charge	$dI/dt=100\text{A}/\mu\text{s}$	-	7	-	nC

### Notes:

1. Pulse width limited by maximum junction temperature.
2. Pulse test - pulse width  $\leq 300\mu\text{s}$ , duty cycle  $\leq 2\%$
3. Surface mounted on 1in<sup>2</sup> copper pad of FR4 board ; 260°C/W when mounted on min. copper pad.

THIS PRODUCT IS SENSITIVE TO ELECTROSTATIC DISCHARGE, PLEASE HANDLE WITH CAUTION.

USE OF THIS PRODUCT AS A CRITICAL COMPONENT IN LIFE SUPPORT OR OTHER SIMILAR SYSTEMS IS NOT AUTHORIZED.

APEC DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

APEC RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN.



## Typical Electrical Characteristics




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. On-Resistance vs.  
Gate Voltage




Fig 4. Normalized On-Resistance  
vs. Junction Temperature




Fig 5. Forward Characteristic of  
Reverse Diode




Fig 6. Gate Threshold Voltage vs.  
Junction Temperature



## Typical Electrical Characteristics (cont.)




Fig 7. Gate Charge Characteristics




Fig 8. Typical Capacitance Characteristics




Fig 9. Maximum Safe Operating Area




Fig 10. Effective Transient Thermal Impedance




Fig 11. Switching Time Waveform






Fig 12. Gate Charge Waveform



## Package Dimensions: SOT-363




SYMBOLS	Millimeters		
	MIN	NOM	MAX
A	0.80	0.95	1.10
A1	0.00	0.05	0.10
A2	0.70	0.85	1.00
b	0.15	0.25	0.35
C	0.05	0.15	0.25
D	1.80	2.00	2.20
E1	1.15	1.25	1.35
E	1.80	2.15	2.50
e	0.65 (ref.)		
L	0.26	0.36	0.46



1. All dimensions are in millimeters.
2. Dimensions do not include mold protrusions.

## Marking Information:



Product: .4U = AP2325GEU6-HF-3

Date/lot code

For details of how to convert this to standard YYWW date code format, please contact us directly.