




Complementary N and P-channel Enhancement-mode Power MOSFETs

Simple Drive Requirement

Low On-resistance

Fast Switching Performance

RoHS-compliant, halogen-free




N-CH	BV_{DSS}	16V
	$R_{DS(ON)}$	58mΩ
	I_D	3.5A
P-CH	BV_{DSS}	-16V
	$R_{DS(ON)}$	125mΩ
	I_D	-2.5A

Description

Advanced Power MOSFETs from APEC provide the designer with the best combination of fast switching, low on-resistance and cost-effectiveness.

The AP2531GY-HF-3 is in a standard SOT-26 package, which is widely used for commercial and industrial surface-mount applications, and is well suited for applications such as small DC and servo motor drives.



Absolute Maximum Ratings

Symbol	Parameter	Rating		Units
		N-channel	P-channel	
V_{DS}	Drain-Source Voltage	16	-16	V
V_{GS}	Gate-Source Voltage	± 8	± 8	V
I_D at $T_A=25^\circ C$	Continuous Drain Current ³	3.5	-2.5	A
I_D at $T_A=70^\circ C$	Continuous Drain Current ³	2.8	-2.0	A
I_{DM}	Pulsed Drain Current ¹	10	-10	A
P_D at $T_A=25^\circ C$	Total Power Dissipation	1.14		W
	Linear Derating Factor	0.01		W/°C
T_{STG}	Storage Temperature Range	-55 to 150		°C
T_J	Operating Junction Temperature Range	-55 to 150		°C

Thermal Data

Symbol	Parameter	Value	Unit
Rthj-a	Maximum Thermal Resistance, Junction-ambient ³	110	°C/W

Ordering Information

AP2531GY-HF-3TR : in RoHS-compliant, halogen-free SOT-26, shipped on tape and reel (3000 pcs/reel)



N-channel Electrical Specifications at $T_j=25^\circ\text{C}$ (unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{\text{GS}}=0\text{V}$, $I_{\text{D}}=250\mu\text{A}$	16	-	-	V
$\Delta \text{BV}_{\text{DSS}}/\Delta T_j$	Breakdown Voltage Temperature Coefficient	Reference to 25°C , $I_{\text{D}}=1\text{mA}$	-	0.01	-	$\text{V}/^\circ\text{C}$
$R_{\text{DS}(\text{ON})}$	Static Drain-Source On-Resistance ²	$V_{\text{GS}}=4.5\text{V}$, $I_{\text{D}}=3\text{A}$	-	-	58	$\text{m}\Omega$
		$V_{\text{GS}}=2.5\text{V}$, $I_{\text{D}}=2\text{A}$	-	-	70	$\text{m}\Omega$
		$V_{\text{GS}}=1.8\text{V}$, $I_{\text{D}}=1\text{A}$	-	-	85	$\text{m}\Omega$
$V_{\text{GS}(\text{th})}$	Gate Threshold Voltage	$V_{\text{DS}}=V_{\text{GS}}$, $I_{\text{D}}=250\mu\text{A}$	0.2	-	1	V
g_{fs}	Forward Transconductance	$V_{\text{DS}}=5\text{V}$, $I_{\text{D}}=3\text{A}$	-	9	-	S
I_{DSS}	Drain-Source Leakage Current	$V_{\text{DS}}=16\text{V}$, $V_{\text{GS}}=0\text{V}$	-	-	1	uA
	Drain-Source Leakage Current ($T_j=70^\circ\text{C}$)	$V_{\text{DS}}=12\text{V}$, $V_{\text{GS}}=0\text{V}$	-	-	25	uA
I_{GSS}	Gate-Source Leakage	$V_{\text{GS}}=\pm 8\text{V}$	-	-	± 100	nA
Q_g	Total Gate Charge ²	$I_{\text{D}}=3\text{A}$	-	7	12	nC
Q_{gs}	Gate-Source Charge		-	0.6	-	nC
Q_{gd}	Gate-Drain ("Miller") Charge		-	2	-	nC
$t_{\text{d}(\text{on})}$	Turn-on Delay Time ²	$V_{\text{DS}}=10\text{V}$	-	6	-	ns
t_r	Rise Time	$I_{\text{D}}=1\text{A}$	-	11	-	ns
$t_{\text{d}(\text{off})}$	Turn-off Delay Time		-	17	-	ns
t_f	Fall Time		-	3	-	ns
C_{iss}	Input Capacitance	$V_{\text{GS}}=0\text{V}$	-	365	585	pF
C_{oss}	Output Capacitance		-	70	-	pF
C_{rss}	Reverse Transfer Capacitance		-	60	-	pF
R_g	Gate Resistance	$f=1.0\text{MHz}$	-	1.4	2	Ω

Source-Drain Diode

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
V_{SD}	Forward On Voltage ²	$I_{\text{S}}=0.9\text{A}$, $V_{\text{GS}}=0\text{V}$	-	-	1.3	V

Notes:

1. Pulse width limited by maximum junction temperature.
2. Pulse width $\leq 300\text{us}$, duty cycle $\leq 2\%$.
3. Surface mounted on 1 in² copper pad of FR4 board, $t \leq 10\text{sec}$; $180^\circ\text{C}/\text{W}$ when mounted on min. copper pad.

THIS PRODUCT IS SENSITIVE TO ELECTROSTATIC DISCHARGE, PLEASE HANDLE WITH CAUTION.

USE OF THIS PRODUCT AS A CRITICAL COMPONENT IN LIFE SUPPORT OR OTHER SIMILAR SYSTEMS IS NOT AUTHORIZED.

APEC DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

APEC RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN.



P-channel Electrical Specifications at $T_j=25^\circ\text{C}$ (unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{\text{GS}}=0\text{V}$, $I_{\text{D}}=-250\mu\text{A}$	-16	-	-	V
$\Delta \text{BV}_{\text{DSS}}/\Delta T_j$	Breakdown Voltage Temperature Coefficient	Reference to 25°C , $I_{\text{D}}=-1\text{mA}$	-	0.01	-	$\text{V}/^\circ\text{C}$
$R_{\text{DS(ON)}}$	Static Drain-Source On-Resistance	$V_{\text{GS}}=-4.5\text{V}$, $I_{\text{D}}=-2\text{A}$	-	-	125	$\text{m}\Omega$
		$V_{\text{GS}}=-2.5\text{V}$, $I_{\text{D}}=-1.6\text{A}$	-	-	165	$\text{m}\Omega$
		$V_{\text{GS}}=-1.8\text{V}$, $I_{\text{D}}=-1\text{A}$	-	-	210	$\text{m}\Omega$
$V_{\text{GS(th)}}$	Gate Threshold Voltage	$V_{\text{DS}}=V_{\text{GS}}$, $I_{\text{D}}=-250\mu\text{A}$	-0.2	-	-1	V
g_{fs}	Forward Transconductance	$V_{\text{DS}}=-5\text{V}$, $I_{\text{D}}=-2\text{A}$	-	5	-	S
I_{DSS}	Drain-Source Leakage Current	$V_{\text{DS}}=-16\text{V}$, $V_{\text{GS}}=0\text{V}$	-	-	-1	uA
	Drain-Source Leakage Current ($T=70^\circ\text{C}$)	$V_{\text{DS}}=-12\text{V}$, $V_{\text{GS}}=0\text{V}$	-	-	-25	uA
I_{GSS}	Gate-Source Leakage	$V_{\text{GS}}=\pm 8\text{V}$	-	-	± 100	nA
Q_g	Total Gate Charge ²	$I_{\text{D}}=-2\text{A}$	-	6	10	nC
Q_{gs}	Gate-Source Charge	$V_{\text{DS}}=-10\text{V}$	-	0.8	-	nC
Q_{gd}	Gate-Drain ("Miller") Charge	$V_{\text{GS}}=-4.5\text{V}$	-	2	-	nC
$t_{\text{d(on)}}$	Turn-on Delay Time ²	$V_{\text{DS}}=-10\text{V}$	-	7	-	ns
t_r	Rise Time	$I_{\text{D}}=-1\text{A}$	-	20	-	ns
$t_{\text{d(off)}}$	Turn-off Delay Time	$R_G=3.3\Omega$, $V_{\text{GS}}=-5\text{V}$	-	23	-	ns
t_f	Fall Time	$R_D=10\Omega$	-	24	-	ns
C_{iss}	Input Capacitance	$V_{\text{GS}}=0\text{V}$	-	380	610	pF
C_{oss}	Output Capacitance	$V_{\text{DS}}=-10\text{V}$	-	90	-	pF
C_{rss}	Reverse Transfer Capacitance	$f=1.0\text{MHz}$	-	75	-	pF
R_g	Gate Resistance	$f=1.0\text{MHz}$	-	8	12	Ω

Source-Drain Diode

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V_{SD}	Forward On Voltage ²	$I_{\text{S}}=-0.9\text{A}$, $V_{\text{GS}}=0\text{V}$	-	-	-1.3	V

Notes:

1. Pulse width limited by maximum junction temperature.
2. Pulse width $\leq 300\text{us}$, duty cycle $\leq 2\%$.
3. Surface mounted on 1 in² copper pad of FR4 board, $t \leq 10\text{sec}$; $180^\circ\text{C}/\text{W}$ when mounted on min. copper pad.

THIS PRODUCT IS SENSITIVE TO ELECTROSTATIC DISCHARGE, PLEASE HANDLE WITH CAUTION.

USE OF THIS PRODUCT AS A CRITICAL COMPONENT IN LIFE SUPPORT OR OTHER SIMILAR SYSTEMS IS NOT AUTHORIZED.

APEC DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

APEC RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN.



Typical N-channel Electrical Characteristics




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. On-Resistance vs. Gate Voltage




Fig 4. Normalized On-Resistance vs. Junction Temperature




Fig 5. Forward Characteristic of Reverse Diode




Fig 6. Gate Threshold Voltage vs. Junction Temperature



Typical N-channel Electrical Characteristics (cont.)




Fig 7. Gate Charge Characteristics




Fig 8. Typical Capacitance Characteristics




Fig 9. Maximum Safe Operating Area




Fig 10. Effective Transient Thermal Impedance




Fig 11. Transfer Characteristics




Fig 12. Gate Charge Waveform



Typical P-channel Electrical Characteristics




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. On-Resistance vs. Gate Voltage




Fig 4. Normalized On-Resistance vs. Junction Temperature




Fig 5. Forward Characteristic of Reverse Diode




Fig 6. Gate Threshold Voltage vs. Junction Temperature



Typical P-channel Electrical Characteristics (cont.)




Fig 7. Gate Charge Characteristics




Fig 8. Typical Capacitance Characteristics




Fig 9. Maximum Safe Operating Area




Fig 10. Effective Transient Thermal Impedance




Fig 11. Transfer Characteristics






Fig 12. Gate Charge Waveform



Package Dimensions: SOT-26



SYMBOLS	Millimeters		
	MIN	NOM	MAX
A	2.70	2.90	3.10
B	2.60	2.80	3.00
C	1.40	1.60	1.80
D	0.30	0.43	0.55
E	0.00	0.05	0.10
H	1.20REF		
G	1.90REF		
I	0.12REF		
J	0.37REF		
L	0.95REF		



1. All dimensions are in millimeters.
2. Dimensions do not include mold protrusions.

Marking Information: SOT-26

Laser Marking

