

# SPECIFICATION FOR APPROVAL

CUSTOMER:		DATE:	
PART NO: SPI0705-331M		DWG.NO:	
CUSTOMER PART NO:		CUST.DWG.NO:	
<p>(1) DIMENSION(UNIT: mm)</p> <div style="text-align: center;"> </div>		A	7.0 ± 0.2 m/m
		C	4.5 ± 0.3 m/m
		D	4.9 (REF) m/m
		E	2.0 (REF) m/m
		F	m/m
		G	m/m
		H	m/m
		I	m/m
		J	m/m
		K	m/m
		(2)ELECTRICAL REQUIREMENTS	
L (uH)	330 ± 20%		
RDC (Ω)	0.85 (MAX)		
IDC (A)	0.36 (MAX)		
TEST CONDITION	1KHZ / 0.5V		
		APPROVED BY	
		CHECKED BY	
		DRAWN BY	

# TEST DATA

CUSTOMER:				DATE:			
PART NO: SPI0705-331M				DWG.NO:			
CUSTOMER PART NO :				CUST.DWG.NO :			
TEST CONDITION: 1KHZ / 0.5V				DIMENSION (UNIT : mm)			
ITEM	L (uH)	RDC (Ω)	IDC (A)	A	C		
SPEC	330 ± 20%	0.85 (MAX)	0.36 (MAX)	7.0 ± 0.2	4.5 ± 0.3		
1	319	0.781	OK	6.97	4.60		
2	321	0.777	OK	6.96	4.53		
3	326	0.779	OK	6.93	4.53		
4	324	0.781	OK	6.97	4.52		
5	317	0.783	OK	6.97	4.54		
6	321	0.777	OK	6.89	4.61		
7	324	0.778	OK	6.93	4.55		
8	326	0.780	OK	6.91	4.57		
9	318	0.781	OK	6.98	4.55		
10	322	0.776	OK	6.95	4.56		
$\bar{X}$	321.8	0.78		6.95	4.56		
R	9	0.01		0.09	0.09		
TEST INSTRUMENTS DV-6021 LCR METER VR-131 RDC METER VR116+VR7220 BA/S CURRENT				APPROVED BY			
				CHECKED BY			
				DRAWN BY			