










# E.P.A. GROUNDING CORDS AND ACCESSORIES

Art. 601		Straight wire 3m, 1MOhm resistor, from female protected button 10mm to ring end 5mm
Art. 601/BANANA		Ground cord 3m, 1MOhm resistor from banana 4mm to ring end 5mm
Art. 602/BOTTONE		Ground cord 2m, button female 10mm - button female 10mm-no resistor
Art. 603/20 Art. 603/32		20cm connection cord, 2 protected button female 10mm-no resistor 32cm connection cord, 2 protected button female 10mm-no resistor
Art. 604/M10 Art. 604/F10		Set of 100 push buttons diam. 10mm (50 male+50 female)
Art. 606/10F Art. 606/10M		Connection banana 4mm, w/10mm, or 7mm female pushbuttons
Art. 607 COCCO		Crocodile 1/4" for banana 4mm
Art. 608		Coiled wire 3m, 1 MOhm resistor, from female protected button 10mm to banana 4mm + croco
Art. CPG 900 NEW		Earth wire 3.6m, with 2 banana 4mm insertion, 1 MOhm.



## MULTIPLE PROTECTED BOND

**Art. 610**  
Protected connector includes 1 female 10mm snap, 1 male 10mm snap and 1 banana 4mm snap. Designed for grounding connection.



## GROUNDING POINT

**Art. CPG 4020**  
The CPG 4020 (wired to ground by a 2m ground cord) is designed for applications where mains are inaccessible. One M5 post is placed in front for grounding. Dim. 40mm x 45mm x 12mm. ESD symbol.

## COMMON POINT TO GROUND

### CPG 1020 Serie

CPG 1020 is a double wristband earth bonding point suitable for any kind of workstation. Easily mountable under the table tops, but also on any metal frame on equipments. **CPG 1020** is available with different combinations of plugs and rest button when the cord is disconnected.

Standard version:

**Art. CPG 1020:** 2 banana plugs 4 mm, 2 male buttons 10 mm, 2 male buttons 4 mm, dimensions 80x38x30 mm.



Art. CPG 1020

Art. CPG 1020 SAFETY



## EARTH SAFE PLUG

### Art. CPG 2000

Adaptor safety plug designed for ESD equipment, including 1 meg safety resistor and LED: the green LED advises if the earth connection is ok. If the earth is disconnected the LED turns off and a buzzer sounds. Connections through a 10 mm pressbutton and eventually an adaptor for 4 mm banana plug.



## EUROPEAN EARTH BONDING POINTS

### Serie CPG 3000

Designed for direct connection to mains earth facilities into the E.P.A. of ground cords and instruments. Two standard models available, both with 1 Mohm safety resistor included.

**Art. CPG 3000 10 M** 3x 10 mm male pressbuttons, Schuko plug

**Art. CPG 3000 10M/1R** 2x 10 mm male pressbuttons, 1x4mm M5 ring receptacle, Schuko plug

Other plugs sortments on request, subject to minimum quantities, please ask.

