



OptoSupply

Light It Up

2.0x1.25x0.8mm Chip LED

OSXX0805C1E

Ver.A.6

■Features

- Single chip
- 2.0x1.25x0.8mm(0805) standard package.
- Suitable for all SMT assembly methods.
- Compatible with infrared and vapor phase reflow solder process.
- This product doesn't contain restriction Substance, comply ROHS standard.
- Compatible with automatic placement equipment.

■Applications

- Automotive : Dashboards, stop lamps, turn signals.
- Backlighting : LCDs, Key pads advertising.

■Absolute Maximum Rating

(Ta=25°C)

Item	Symbol 1	Value		Unit
		W5/M5 /B5/K5/G5	R5/G8 /Y5/O5	
DC Forward Current	I _F	30	30	mA
Pulse Forward Current*	I _{FP}	100	100	mA
Reverse Voltage	V _R	5	5	V
Power Dissipation	P _D	108	78	mW
Operating Temperature	Topr	-40 ~ +85		°C
Storage Temperature	Tstg	-40~ +85		°C
Lead Soldering Temperature	Tsol	260°C/10sec		-

*Pulse width Max 0.1ms, Duty ratio max 1/10

■Electrical -Optical Characteristics

(Ta=25°C)

Part Number	Color	V _F (V)			I _R (μA)	Iv(mcd)			λD(nm)			2θ1/2(deg)
		Min.	Typ.	Max.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.	Typ.
		I _F =20mA			V _R =5V	I _F =20mA						
OSW50805C1E	White	W5	-	3.3	3.6	10	350	450	-	X:0.27, Y:0.28		120
OSM50805C1E	Warm White	M5	■	-	3.3	3.6	10	350	450	-	X:0.44, Y:0.41	120
OSK50805C1E	Pink	K5	■	-	3.3	3.6	10	60	90	-	X:0.38, Y:0.18	120
OSB50805C1E	Blue	B5	■	-	3.2	3.6	10	80	120	-	460 465 475	120
OSG50805C1E	True Green	G5	■	-	3.3	3.6	10	400	450	-	520 525 530	120
OSG80805C1E	Yellow Green	G8	■	-	2.0	2.6	10	20	35	-	564 570 578	120
OSY50805C1E	Yellow	Y5	■	-	2.1	2.6	10	100	120	-	585 590 595	120
OSO50805C1E	Orange	O5	■	-	2.0	2.6	10	100	120	-	600 605 610	120
OSR50805C1E	Red	R5	■	-	2.0	2.6	10	120	150	-	620 625 630	120

*1 Tolerance of measurements of chromaticity coordinate is ±10%

*2 Tolerance of measurements of dominant wavelength is ±1nm

*3 Tolerance of measurements of luminous intensity is ±15%

*4 Tolerance of measurements of forward voltage is ±0.1V

LED & Application Technologies



REACH
The new EU chemicals legislation

