SIDE CUTTER, COMBINATION PLIERS, PLIERS ADJUSTMENT

lap joint • chromed

bicoloured hand guard

			Cutting capacity				
No.	Length	Headwidth	Finish	Wire	mm	Ø	Weight
	mm	mm		soft	medium	hard	g
Side cutt	ers						
swedish d	esign						
3-132-16	130	17		3.0	2.0	1.0	135
3-133-16	145	18		4.0	2.5	1.3	165
Side cutte	ers						
		sm for single-	core and mul	lti-core v	vire 1.5 a	and 2.5	mm ²
		sm for single-	core and mul	ti-core v 4.0	vire 1.5 a	and 2.5	mm ²
with stripp	ping pri	22	core and mul				
with stripp 3-135-16 Power sig	ning pri 175 de cutt	22		4.0	2.5		
with stripp 3-135-16 Power sig	175 de cutt handy	22 eers model, with ex		4.0	2.5		
with stripp 3-135-16 Power side powerful,	ing pri 175 de cutt handy vire, spe	22 eers model, with ex		4.0	2.5		
with stripp 3-135-16 Power side powerful, for steel w	175 de cutt handy vire, spe	22 eers model, with ex		4.0	2.5	1.3	





No.	Ler mm	ngth Headwi	Finish dth	Weight g
Combina	tion pl	iers		
with wire	cutter,	for hard	wire	
(lap joint)				
3-732-16	165	23		205
3-733-16	180	25		245
Adjusting	pliers	6		
straight, fl	at and	wide		
(lap joint)				
3-335-16	135	13		95
Adjusting	pliers	6		
straight, p	ointed	nose		
(lap joint)				
3-345-16	135	13		95







WIRE STRIPPERS

Lap joint - bicoloured hand guard

INO.	Ler	igiri	FINISH	vveigni
	mm	Headw	idth	g
"Record"	wire s	trippe	rs	
Spring sys	stem e	nables	safe working with automatic adjustment to	o the
wire size.	Easy to	use: ir	nsert wire - close pliers - remove insulation	
3-805-16	160	-	for wire thicknesses from 0.5 to 5 mm Ø nickel-plated	180
Wire strip	opers v	vith ac	ljusting screw	
for all wire	e thickn	esses,	with compression spring	
3-815-16	155	-	chrome-plated	170







PRESSING PLIERS

lay on joint

No.	Length	Finish	Weight
	mm Hea	dwidth	g
Pressing	pliers for n	nulticore cable end	
combined	d with cable	cutter and stripping-prism for o	different
cable dim	ensions for	sleeves of 0.25 - 2.5 mm2.	
3-871-6	155 -	nickel-plated, with red insulation	165
Pressing	pliers for n	nulticore cable end	
combined	d with cable	cutter and stripping-prism for o	different
cable dim	ensions for	sleeves of 0.50 - 16.0 mm2.	





110