ENGINEERS'S TWEEZERS AND SET FOR SPECIAL TWEEZERS

No.	Length mm	Length Inch	Finish	Weight g
Component tweezers				
made from steel, with insulated jaws, a special tool for easy insertion and removal of plug-in transistors of various sizes				
5-006	140	5 1/2"	nickel-plated	23
Component tweezers				
made from steel, with semi-circular jaws, 5 mm wide, to facilitate the insertion and removal of horizontally positioned components of various sizes				
5-007	140	5 1/2"	nickel-plated	25
Component tweezers				
made from steel, with jaws bent inwards at right angles, 5 mm wide, to facilitate the removal of round or cube-shaped components				
5-008	140	5 1/2"	nickel-plated	23
Component tweezers				
made from steel, with insulated jaws, 5.5 mm wide, for gripping flat components				
5-009	140	5 1/2"	nickel-plated	22
Heat dissipating tweezers				
made from steel, for use when soldering transistors, gold-bonded diodes etc., the flat, wide points of the tweezers are narrow and provided with copper jaws				
5-115	165	6 1/2"	nickel-plated	35
Jewellerie's tweezers				
made from steel, fine-rounded tips, with X-serration				
5-119	140	5 1/2"	nickel-plated	19
Sheet-metal tweezers				
straight, flat and pointed				
5-125	110	4 3/8"	nickel-plated	12
Sheet-metal tweezers				
with sliding fastener for a firm grip, straight, with narrow pointed tips				
5-126	160	4 1/4"	nickel-plated	22
IC-tweezers				
for gripping, insertion and removal of IC's				
2-601	125	5"	nickel-plated	20

5-100 12-piece set special tweezers and tools

No.	Description of individual tools
2-126	Desoldering lever, slotted at one end, with plastic handle, 115 mm
2-127	Tin knife with plastic handle, 115 mm
2-601	IC-tweezers, nickel-plated, 125 mm, for gripping, inserting and removing of IC,s
5-006	Component tweezers, nickel-plated, with insulated jaws, a special tool for easy insertion and removal of plug-in transistors of various sizes, 140 mm
5-078	Anti-magnetic tweezers, tapering chisel, 1.0 mm width, matt finish, stainless and acid-resistant, 130 mm
5-107	Engineer´s tweezers, made from steel, with bent tips, nickel-plated, 150 mm
5-107-6	Engineer´s tweezers, as above, strong PVC-insulation
5-115	Heat dissipating tweezers, nickel-plated, 165 mm, for soldering transistors, gold-bonded diodes etc.
5-117	Engineer´s tweezers, straight, flat, wide, nickel-plated, 145 mm
5-117-6	Engineer´s tweezers, as above, strong PVC-insulation
5-121	Engineer´s tweezers, straight, with narrow pointed tips, 120 mm, nickel-plated
5-156	Crossed soldering tweezers, (self-locking tweezers), made from steel, with bent tips and gripping well hand-guard, nickel-plated, 160 mm

ENGINEER'S TWEEZERS

No.	Length mm	Length Inch	Finish	Weight g
Engineer's tweezers				
made from steel, with fine, bent tips, finely serrated				
5-107	150	6"	nickel-plated	20
5-107-1	150	6"	polished with antiallergical coating	23
5-107-6	150	6"	nickel-plated, strong PVC-insulated	27
5-107 VDE	150	6"	with VDE insulation	37
5-107-9	150	6"	teflon-coated	22
Engineer's tweezers				
made from steel, heavy type, straight, flat and wide, tips with serration				
5-117	145	5 3/4"	nickel-plated	25
5-117-1	145	5 3/4"	polished with antiallergical coating	26
5-117-6	145	5 3/4"	nickel-plated, strong PVC insulated	31
5-117 VDE	145	5 3/4"	with VDE insulation	39
5-117-9	145	5 3/4"	teflon-coated	29
Engineer's tweezers				
made from steel, straight, with narrow pointed tips, finely serrated				
5-121	120	4 3/4"	nickel-plated	14
5-121-1	120	4 3/4"	polished with antiallergical coating	14
5-121-6	120	4 3/4"	nickel-plated, strong PVC insulated	17
5-121 VDE	120	4 3/4"	with VDE insulation	13
5-122-9	155	6 1/8"	teflon-coated	24
Crossed tweezers (self-locking tweezers)				
made from steel, jaws 5 mm wide, finely serrated				
5-155	160	6 1/4"	nickel-plated	35
5-155-1	160	6 1/4"	polished with antiallergical coating	36
Crossed soldering tweezers (self-locking tweezers)				
made from steel, with bent tips and gripping well hand guard				
5-156	160	6 1/4"	nickel-plated	29