

SPECIAL ELECTRONIC PLIERS

Black burnished, Double leaf spring
with orange coloured insulation

CUTTING PLIERS

No.	Length mm	Headwidth mm	Finish	Cutting capacity			Weight g
				Wire soft	mm medium	Ø hard	

Side cutters

with slim, rounded head

3-901-12	120	12	with side face	1,5	1.0	0,4	65
----------	-----	----	----------------	-----	-----	-----	----

Side cutters

with slim, pointed head, special flat cutting edge,
for soft wire only

3-902-12	120	12	Flush	1,5	0.8	-	65
----------	-----	----	-------	-----	-----	---	----

Top cutters

with 3 mm wide cutting edge, jaw length 20 mm, for flush
cutting, for soft wire only

3-905-12	135	13	Flush	0,8	0.6	-	75
----------	-----	----	-------	-----	-----	---	----

End cutters

with angular tips and oblique cutting edge, for flush cutting,
for soft wire only

3-906-12	125	13	Flush	0.8	0.6	-	75
----------	-----	----	-------	-----	-----	---	----

ROUND-FLAT-SNIPE NOSE PLIERS

No.	Length		Finish	Weight g
	mm	Headwidth		

Round nose pliers with short jaws

3-931-12	120	12	plain jaws	70
----------	-----	----	------------	----

Flat nose pliers with short jaws

3-932-12	120	10,5	plain jaws	60
----------	-----	------	------------	----

Snipe nose pliers with short jaws

3-933-12	125	11,5	plain jaws	60
----------	-----	------	------------	----

Flat nose pliers slim model, with long jaws

3-942-12	145	12	Serrated jaws	90
----------	-----	----	---------------	----

Snipe nose pliers slim model, with long jaws

3-943-12	145	12	Serrated jaws	80
----------	-----	----	---------------	----

Snipe nose pliers angular, slim model, with long jaws

3-945-12	145	12,5	Serrated jaws	85
----------	-----	------	---------------	----



SPECIAL ELECTRONIC PLIERS

SLIMline

box joint • chrome-plated
compression spring • with transparent insulation

COMPONENT PLIERS

For bending, cutting and squeezing
connecting wires on components

No.	Length		Finish	Weight g
	mm	Headwidth		

Crimping and bending pliers

crimp the wire in one operation without changing
the parallelism of the ends of the wire

3-172-2	130	11,5	super-slim model	70
---------	-----	------	------------------	----



CUTTING PLIERS

No.	Length mm	Headwidth mm	Finish	Cutting capacity			Weight g
				Wire soft	mm medium	Ø hard	

Micro side cutters

with slim, pointed head

3-125-2	115	10,5	Semi flush	1,5	1.0	0,3	60
---------	-----	------	------------	-----	-----	-----	----

SLIMline-Side cutters

with slim, rounded head

3-127-2	115	12	Semi flush	1,5	1.0	0,4	60
---------	-----	----	------------	-----	-----	-----	----

SLIMline-Side cutters

with slim, rounded head,
with wire retaining spring (to hold the wire clippings)

3-127-2 DR	115	12	Semi flush	1,6	1,2	0,5	60
------------	-----	----	------------	-----	-----	-----	----

SLIMline-oblique top cutters

with slim head, for flush cutting,
for soft wire only

3-128-2	120	11,5	Flush	2,0	1,5	0,3	70
---------	-----	------	-------	-----	-----	-----	----



SPECIAL ELECTRONIC PLIERS

SLIMline

box joint - chrome plated

compression spring - transparent insulation

ROUND-FLAT-SNIPE NOSE PLIERS

No.	Length		Finish	Weight
	mm	Headwidth		
Micro round nose pliers extremely light and slim				
3-435-2	120	9.5	plain jaws	45
Micro flat nose pliers extremely light and slim				
3-445-2	120	9.5	plain jaws	50
Micro snipe nose pliers extremely light and slim				
3-455-2	120	10	plain jaws	50
Round nose pliers slim model, with compression spring and plain jaws				
3-461-2	130	12	short jaws	70
Flat nose pliers slim model, with compression spring and plain jaws				
3-462-2	130	12	short jaws	80
3-472-2	145	12	long jaws	85
Snipe nose pliers slim model, with compression spring and plain jaws				
3-463-2	130	12	short jaws	75
3-473-2	145	12	long jaws	85
Snipe nose pliers				
angular, slim model, with compression spring and plain jaws				
3-481-2	130	9	short jaws	50
3-482-2	140	12	long jaws	90



CUTTING TOOLS

No.	Length		Finish	Weight
	mm	Headwidth		
Cabel cutters				
especially for coaxial cable, robust execution with closed lock, for cable up to 10.5 mm Ø				
3-0648	160	-	burnished-insulated	150
Electronics side cutters				
with spring, without side face, for CU-wires up to 1.0 mm Ø				
3-0641	130	-	burnished-insulated	70
Stripping side cutters				
standard-execution, without side face, with spring, for CU-wires up to 0.8 mm Ø				
3-0645	125	-	burnished-insulated	60

